



NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

BILL RICHARDSON

Governor

Joanna Prukop

Cabinet Secretary

Lori Wrotenbery

Director

Oil Conservation Division

ADMINISTRATIVE ORDER NO. WFX-796

***APPLICATION OF MERIT ENERGY COMPANY TO EXPAND ITS WATERFLOOD
PROJECT IN THE GRAYBURG-JACKSON (SEVEN RIVERS-QUEEN-GRAYBURG-SAN
ANDRES) POOL IN EDDY COUNTY, NEW MEXICO***

**ADMINISTRATIVE ORDER
OF THE OIL CONSERVATION DIVISION**

Under the provisions of Division Order No. R-3185, as amended, Merit Energy Company has made application to the Division on September 18, 2003 for permission to expand its Turner "B" Waterflood Project in the Grayburg-Jackson (Seven Rivers-Queen-Grayburg-San Andres) Pool in Eddy County, New Mexico.

RECEIVED

JAN 18 2004

OCD-ARTESIA

THE DIVISION DIRECTOR FINDS THAT:

- (1) The application was filed in due form.
- (2) Satisfactory information was provided that all offset operators have been duly notified of the application.
- (3) No objection has been received within the waiting period as prescribed by Rule 701(B).
- (4) The proposed injection well is eligible for conversion to injection under the terms of Rule 701.
- (5) The proposed expansion of the above referenced waterflood project will not cause waste nor impair correlative rights.

IT IS THEREFORE ORDERED THAT:

The applicant, Merit Energy Company, is hereby authorized to inject water into the Seven Rivers formation, Grayburg-Jackson (Seven Rivers-Queen-Grayburg-San Andres Pool,) through the interval from approximately 1,874 feet to 2,022 feet using 2-3/8-inch plastic lined tubing set in a packer located within 100 feet of the uppermost injection perforations in the following described well for purposes of secondary recovery to wit:

Turner "B" Well No. 12 (API No. 30-015-05284)
2080' FSL & 660' FWL (Unit L) Section 20, Township 17 South, Range 31 East
Injection Interval: Open-Hole 1,874 feet to 2,022 feet
Maximum Surface Injection Pressure: 375 psi

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

Prior to commencing injection operations into the Turner "B" Well No. 12, the applicant shall cement the following-described wells above, across and below the injection interval to assure that these wellbores will not provide an avenue of escape for injected fluid, in a manner that is satisfactory to the supervisor of the Division's Artesia District Office:

Fren Oil Co. No. 13, API No. 30-015-05261, 660' FSL & 710' FEL (Unit P) 19-17S-31E
Turner "B" No. 44, API No. 30-015-05311, 660' FSL & 2055' FWL, (Unit N) 20-17S-31E

Subsequent to the completion of remedial cement operations on the area of review wells described above, the applicant shall submit documentation to the Santa Fe Office of the Division verifying that this work has been completed. This documentation shall be in the form of a cover letter addressed to the Engineering Bureau complete with all applicable Form C-103's (Sundry Notices). Failure to comply with this directive may result in the cancellation of injection authority.

Prior to commencing injection operations into the well, the casing shall be pressure tested from the surface to the packer setting depth to assure the integrity of said casing.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing or packer.

The injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure to 0.2 psi per foot of depth to the uppermost injection perforations or open-hole interval.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Grayburg-Jackson (Seven Rivers-Queen-Grayburg-San Andres) Pool. Such

proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Artesia district office of the Division of the date and time: i) remedial cement operations will be conducted on each of the wells described above; ii) of the installation of injection equipment in the injection well; and iii) of the mechanical integrity test so that these operations may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Artesia District Office of the Division of the failure of the tubing, casing or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.


The subject well shall be governed by all provisions of Division Order No. R-3185, as amended, and Rules 702-706 of the Division Rules and Regulations not inconsistent herewith.

PROVIDED FURTHER THAT, jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

DONE at Santa Fe, New Mexico, on this 5th day of January, 2004.

STATE OF NEW MEXICO
OIL CONSERVATION DIVISION



LORI WROTENBERY
Director

S E A L