

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1006 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38109
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No L-3355
7. Lease Name or Unit Agreement Name Parkway 16 State Com
8. Well Number 2H
9. OGRID Number 14744
10. Pool name or Wildcat Scanlon Draw; Bone Spring 55510

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: ☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter D : 200 feet from the North line and 350 feet from the West line
Section 21 Township 19S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RI, GR, etc.)
3330' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER Change Csg Design ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Mewbourne Oil Company has an approved APD for the above captioned well. After further Geological review, we would like to change the casing program as follows:

0 - 300' Fresh water mud spud mud w/line for pH & LCM as needed. Drill 12 1/4" hole. Run 9 5/8" 36# J55 ST & C csg & cement to surface

300' - 8150' Brine water w/line for pH & LCM as needed. Drill 8 1/2" hole. Run 7" 26# P110 LT & C & Butt csg & cement to surface.

8150' - 12100' Inner Fresh water w/polymer mud. Drill 6 1/2" hole. Run 4 1/2" 11.6# P110 liner w/pkrs & ports from 7950' - 12100.

Spud Date

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 08/27/10

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Geologist DATE 10/06/10

Conditions of Approval (if any):