

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-23960
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name NDDUP Unit
8. Well Number 55
9. OGRID Number 025575
10. Pool name or Wildcat Dagger Draw; Upper Penn, North
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3588'GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other P&A	
2. Name of Operator Yates Petroleum Corporation	
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210	
4. Well Location Unit Letter C : 660 feet from the North line and 1980 feet from the West line Section 19 Township 19S Range 25E NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3588'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/6/10 - NU BOP.

10/7/10 - RIH with GR/JB to 7726'. Set a 5-1/2" 10k Alpha CIBP at 7726'. Loaded and tested casing to 500 psi, good. Put 35' cement on top of CIBP.

10/11/10 - Loaded hole with mud gel from 7691' to surface. Pumped 25 sx Class "C" cement at 5546'. Est TOC at 5298'. Did not have to tag. Pumped 25 sx Class "C" cement at 3555'. Est TOC at 3307'. Did not have to tag. Pumped 25 sx Class "C" cement at 1255'. Est TOC at 1007' across intermediate shoe.

10/12/10 - Tagged cement plug at 985'. Perforated 4 holes at 450'. Broke circulation up 5-1/2" x 8-5/8" casing. Circulated 110 sx to surface. ND BOP. Cement was not there. Tried to top well off. Pumped 50 more sx Class "C" cement. Did not fill up. WOC 3 hrs. Tagged cement at 443'. Topped well off in casing with 45 sx Class "C" cement. Tied onto 8-5/8" casing. Topped off with 60 sx Class "C" cement.

10/20/10 - Dug out cellar. Installed dry hole marker. Filled cellar back in and dug up anchors. Cleaned location. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

RECEIVED
OCT 27 2010
NMOCD ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE October 21, 2010

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE [Signature] DATE 10/28/2010

Conditions of Approval (if any):

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms: www.emsrd.state.nm.us/oed.

COB ✓