Submit 1 Copy To Appropriate District State of New Me	
Office Energy, Minerals and Natu	iral Resources October 13, 2009 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II OIL CONSERVATION	N DIVISION 30-015-38047
1301 W. Grand Ave., Artesia, NM 88210 District III 1220 South St. Fra	ancis Dr. 5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 8	
1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No. 648
SUNDRY NOTICES AND REPORTS ON WEL	1
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN (DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-10 PROPOSALS.)	
1. Type of Well: Oil Well 🗓 Gas Well 🗌 Other	8. Well Number 236
2. Name of Operator	9. OGRID Number
Stephens & Johnson Operating Co	019958
3. Address of Operator P 0 Box 2249, Wichita Falls, TX 76307	10. Pool name or Wildcat Millman-Yates-SR-QN-GB-SA East
4. Well Location	
Unit Letter <u>A</u> : 1290 feet from the Nor	rth line and 330 feet from the East line
Section 14 Township 19S Range 28E NMPM County Eddy	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3410' KB; 3398' GR	
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK D PLUG AND ABANDON D	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS. COMMEN
PULL OR ALTER CASING	CASING/CEMENT JOB RECEIVED
DOWNHOLE COMMINGLE	DEC 3 0 2010
OTHER:	OTHER: Completion NMOCD ARTESIA X
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
October 4, 2010: Pressure tested 5 1/2" 15.50 #/ft casing to 1500 psi for 30 minutes. Held OK. Perforated one shot at each of the following depths: 2199, 2202, 2205, 2208, 2211, 2241, 2252, 2301, 2304, 2307, 2310, 2379, 2382, 2385, 2422, 2425, 2428, 2431, 2446, 2449, 2452, 2455. October 7, 2010: Acidized perforations with 2500 gals 15% NEFE acid. December 13, 2010: Sand fraced perforations with 70,000 lbs 16/30 brown sand and 42,000 gals gel. December 15, 2010: Put well on production.	

Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge and belief. DATE\_

<u>Petroleum Engineer</u>

mkincaid@sjoc.net Type or print name William M. Kincaid

PHONE 940-723-2166 E-mail address: \_

For State Use Only

Brows TITLE FIRM SUPPRISON DATE 1-3-11

submit sundry to include the detail-size, wt., grd., # of jts in hole-