
Hydrogen Sulfide Drilling Operations Plan Bluetail 8 Federal No. 2

Cimarex Energy Co. of Colorado

Unit E, Section 8 T17S R29E, Eddy County, NM 30-015-38454

1 All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:

- A. Characteristics of H₂S
- B. Physical effects and hazards
- C. Proper use of safety equipment and life support systems.
- D. Principle and operation of H₂S detectors, warning system and briefing areas.
- E. Evacuation procedure, routes and first aid.
- F. Proper use of 30 minute pressure demand air pack.



2 H₂S Detection and Alarm Systems:

A. H₂S detectors and audio alarm system to be located at bell nipple, end of flow line (mud pit) and on derrick floor or doghouse.

3 Windsock and/or wind streamers:

- A. Windsock at mudpit area should be high enough to be visible.
- B. Windsock at briefing area should be high enough to be visible.

4 Condition Flags and Signs:

- A. Warning sign on access road to location.
- B. Flags to be displayed on sign at entrance to location. Green flag indicates normal safe condition. Yellow flag indicates potential pressure and danger. Red flag indicates danger (H₂S present in dangerous concentration). Only emergency personnel admitted to location.

5 Well control equipment:

A. See exhibit "E"

6 Communication:

- A. While working under masks chalkboards will be used for communication.
- B. Hand signals will be used where chalk board is inappropriate.
- C. Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.

7 Drillstem Testing:

No DSTs or cores are planned at this time.

- 8 Drilling contractor supervisor will be required to be familiar with the effects H₂S has on tubular goods and other mechanical equipment.
- 9 If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas seperator will be brought into service along with H₂S scavengers if necessary.

H₂S Contingency Plan **Bluetail 8 Federal No. 2** Cimarex Energy Co. of Colorado Unit E, Section 8 T17S R29E, Eddy County, NM

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must:

- ★ Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- ★ Evacuate any public places encompassed by the 100 ppm ROE.
- ★ Be equipped with H₂S monitors and air packs in order to control the release.
- ★ Use the "buddy system" to ensure no injuries occur during the response.
- ★ Take precautions to avoid personal injury during this operation.
- ★ Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- ★ Have received training in the:
 - ♦ Detection of H₂S, and
 - Measures for protection against the gas,
 - ♦ Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO_2) . Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Common	Chemical	Specific	Threshold		Lethal
Name	Formula	Gravity	Limit	Hazardous Limit	Concentration
Hydrogen Sulfide	H₂S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air=1	2 ppm	N/A	1000 ppm

Contacting Authorities

Cimarex Energy Co. of Colorado's personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including directions to site. The following call list of essential and potential responders has been prepared for use during a release. Cimarex Energy Co. of Colorado's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER).

H_2S Contingency Plan Emergency Contacts

Bluetail 8 Federal No. 2

Cimarex Energy Co. of Colorado Unit E, Section 8 T17S R29E, Eddy County, NM

Company Office

Cimarex Energy Co. of Colorado Co. Office and After-Hours Menu 800-969-4789

Key Personnel

Name	Title	Office	Mobile
Doug Park	Drilling Manager	432-620-1934	972-333-1407
Dee Smith	Drilling Super	432-620-1933	972-882-1010
Jim Evans	Drilling Super	432-620-1929	972-465-0564
Roy Shirley	Field Super		432-634-2136

Artesia		
Ambulance	911	
State Police	575-746-2703	
City Police	575-746-2703	
Sheriff's Office	575-746-9888	
Fire Department	575-746-2701	
Local Emergency Planning Committee	575-746-2122	
New Mexico Oil Conservation Division	575-748-1283	

<u>Carlsbad</u>		, <u>2007</u> 27 2000
Ambulance	911	
State Police	575-885-3137	
City Police	575-885-2111	
Sheriff's Office	575-887-7551	
Fire Department	575-887-3798	
Local Emergency Planning Committee	575-887-6544	
US Bureau of Land Management	575-887-6544	

<u>Santa Fe</u>	9 FEET 8 FEET	A PAGE A
New Mexico Emergency Response Commission (Santa Fe)	505-476-9600	
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs	505-827-9126	
New Mexico State Emergency Operations Center	505-476-9635	

ļ	/	
	National Emergency Response Center (Washington, D.C.)	800-424-8802

<u> Medical</u>	
Flight for Life - 4000 24th St.; Lubbock, TX	806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX	806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM	505-842-4433
SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM	505-842-4949

<u>Other</u>	7 t <u>22 s 25 </u>	4 em) il em) 11 em) 17 em) il e
Boots & Coots IWC	800-256-9688 or	281-931-8884
Cudd Pressure Control	432-699-0139 or	432-563-3356
Halliburton	575-746-2757	
B.J. Services	575-746-3569	