Form 9-331 Drawer DD Form Approved. Dec. 1973 UNITED STATES Budget Bureau No. 42-R14 UNITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR MM-25862 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME (Do not use this form for proposals to drill or til deepen of proposals 1. Constant of the proposals (Do not use this form 9-331-C for such proposals 1. ECEIVED BY 8. FARM OR LEASE NAME 8. FARM OR LEASE NAME
UNITED STATES 5. LEASE DEPARTMENT OF THE INTERIOR NM-25862 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME
GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS
reservoir. Use Form 9-331-C for such proposals RECEIVED BY 8. FARM OR LEASE NAME
loles Federal
well well well a other ry FEB 11 1987 9. WELL NO.
2. NAME OF OPERATOR
McClellan Oil Corporation O. C. D. 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR ARTESIA, OFFICE Pecos Slope Abo
P.O. Drawer 730, Roswell, NM 88202 11. SEC., T., R., M., OR BLK. AND SURVEY
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AREA
below.) AT SURFACE: 1980' FNL & 660' FWL 12. COUNTY OR PARISH 13. STATE
AT SURFACE: 1980 FNE & 000 FWL 12. COUNT OR PARISH 13. STATE AT TOP PROD. INTERVAL: Chaves NM
AT TOTAL DEPTH: 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,
REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND V
3953 'sG.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL Image: State of the state
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged & Abandoned as follows:

11/28/84: Set 50 sx Class C cement plug at 2200'. Set 50 sx Class C w/ 2% CaCl₂ plug at 940. Pulled out 8-5/8" casing to surface. Tagged plug at 890' with bailer. Set 50'surface plug. Filled cellar with Ready Mix. Installed Dry Hole Marker.

		Post ID 2 2-8-85 P+4
Subsurface Safety Valve: Manu, ar	nd Type	
18. I hereby certify that the foregoes	le TITLE Operations Mgr. DATE	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	Liability under bond is retained well bore.	APPROVED PETER W. CHESTER FEB. 9 1987 BUREAU OF LAND MANAGEMENT ROSWELL RESOURCE AREA

~

