
## NEW MF CO OIL CONSERVATION COMMIC ON

Santa Fe, New Mexico

### **MISCELLANEOUS NOTICES**



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL		
OTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING  NOTICE OF INTENTION TO PLUG WELL		
OTICE OF INTENTION TO REPAIR WELL			
		XX	
OTICE OF INTENTION TO DEEPEN WELL			
Pa oral 1	., Newackexico April 5 de 19	3 <b>7</b>	
TI O DW GAA	Date		
IL CONSERVATION COMMISSION,			
anta Fe, New Mexico. entlemen:			
ollowing is a notice of intentiton to do certain work as d	escribed below at the		
Filiott et al State Lease B-179	Well No. 1 in NW	<del>YMAY</del>	
Company or Operator Lease  Sec. 18 , T. 88 , R. 23E		•	
Sec. 18 , T. 43 , R. 415	N. M. F. W.,		
Chaves County.			
FILL DETAILS OF PRO	POSED PLAN OF WORK		
FOLLOW INSTRUCTIONS IN THE RULE	S AND REGULATIONS OF THE COMMISSION		
m each congrete strate. Tilling	arrying water, to confine wate in between the stratas with	_	
in each separate strata, filling	in patween the stratas with		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratus with he top of hole with heavy ce pipe four inches in diamete		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratus with he top of hole with heavy ce pipe four inches in diamete		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling the heavy mud laden fluid and on to the mud laden fluid, comenting in plant	in between the stratus with he top of hole with heavy ce pipe four inches in diamete		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling the heavy mud laden fluid and on to the hund laden fluid, comenting in plant	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling the heavy mud laden fluid and on to the heavy fluid, comenting in plants	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling the heavy mud laden fluid and on to the hund laden fluid, comenting in plant	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling heavy mud laden fluid, comenting in plamud laden fluid, comenting in plamand four feet above mean ground l	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling heavy mud laden fluid and on to the mud laden fluid, comenting in pland and four feet above mean ground laden fluid.  Approved	in between the stratas with he top of hole with heavy ce pipe four inches in diamete evel.		
in each separate strata, filling heavy mud laden fluid and on to the mud laden fluid, comenting in pland and four feet above mean ground laden fluid.  Approved	top of hole with heavy ce pipe four inches in diameter ovel.  DUTLICATE  Company of Operator of Company o		
in each separate strata, filling heavy mud laden fluid and on to the mud laden fluid, comenting in pland and four feet above mean ground laden fluid.  Approved	top of hole with heavy ce pipe four inches in diameter ovel.		
in each separate strata, filling heavy mud laden fluid, cementing in pla and four feet above mean ground lapproved	between the stratas with the top of hole with heavy company or on the stratas with the top of hole with heavy company or on the stratas with the top of hole with heavy company or on the stratas with the top of hole with heavy company or on the stratas with the top of hole with heavy company or on the stratas with heavy company or on the strat	er .	
in each separate strata, filling heavy mud laden fluid, cementing in pla and four feet above mean ground laden fluid, sementing in pla and four feet above mean ground laden fluid, sementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid, cementing in pla and four feet above mean ground laden fluid in pla and four feet above mean ground laden fluid in pla and four feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground laden fluid in pla and feet above mean ground fluid in pla and feet above mean ground fluid in pla and feet abo	between the stratas with the top of hole with heavy ce pipe four inches in diameter ovel.  DUTLICATE  Company or Opyator  By  Position Lease Holder	er .	
in each separate strata, filling heavy mud laden fluid and on to the mud laden fluid, cementing in pla and four feet above mean ground l	By Company or Obvator  Position Lease Holder  Send communications regarding we name  Name L. E. Elliott	ell to	
in each separate strata, filling heavy mud laden fluid, cementing in pla and four feet above mean ground laden fluid.  Approved	By Company or Operator  Position Lease Holder  Send communications regarding we	ell to	

ICR.

# AND THE STATE OF SELECTION OF COMMENSE

weadlend it were

### MISSELL AND OF STREET

disa from agricina di sa di estge a como di cua en di colonida a cartificazione, e que fre ci a cartificazione constituente digente, cartificada e la segundo en appei di constituit como segundo e constituitada e e el cara di cartificazione di cartificazione de sa cartificazione di cartificazione de sa cartificazione de sa

# The design of the Carlot of th

en en 1970 en 1980 en En 1980 en 198

### POTE BEIMPRORPENDE, REPENDANCH TOOK

(2) A second of the artists of the description of the description of the description of the description.

en de la composition della com

TO THE STATE OF TH

WELLIN EU

Elliott et al, State

NW1NW1 Section 16 Twp. 85, Rge. 23E

Enaves County, New Mexico

Elevation 3775 feet.

Formation	Color	From	To
Fill Lime Gip Lime, Broken Shale Lime Sandy Shale Lime Sandy Lime (with water) Shale Shale Lime Shale Lime Shale Lime Shale Lime Lime White Sand (with water) Sand Lime Lime	L. Brown L. Brown White Brown Brown L. Gray Yellow Black Brown Blue Sandy Mlack Green Brown D. Brown D. Gray White Blue Black Blue	0 235 270 335 345 420 445 494 500 517 534 557 593 625 670 717 726 733	5 235 270 335 345 420 445 494 500 517 534 553 593 627 726 733 775
Sand (Salt Water)	Gray	775	784

40.

Ellistt et al, State Mythwat Section 16 Twp. 85, Rge. 23E Diaves County, New Yexico Elevation 3775 feet.

1.5 1.4 7.14

oT	From	refet	Formation
ō	С	b. orown	Fill
335	3	avore .i	ites.
270	380	etină	aib
3 <b>3</b> 5	078	TWOIL :	nime, broken
345	335	e rond	Shale
420	34 <b>5</b>	L. Graj	Lime
445	420	wellsY	Sandy Saule
494	445	ASSIL	Lime
500	494	Erown	Sandy bime (with water)
517	00a	olue -	Shale
534	517	Sandy	Snale
55 <b>4</b>	53 <b>4</b>	Hlack	Lime
<b>2</b> 22	554	Green	Shale
593	557	Drown	Lime, soft
325	593	D. Brown	Lime
370	325	D. Gray	Lime
717	. 370	White	Thite Sand (with water)
726	212	Elue	Sand
733	726	31ack	Lime
775	733	Elue	Line
734	775	Tay	Sund (Salt Water)

410.