

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other RE-ENTRY
well well
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980 FNL & 660 FEL, Sec. 25-5S-24E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐

FRACTURE TREAT ☐ ☐

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON* ☐ ☐

(other) Spud & run production casing.

5. LEASE
NM 28297
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Everette 00 Federal JAN
9. WELL NO.
6
10. FIELD OR WILDCAT NAME
Und. Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit H, Sec. 25-T5S-R24E
12. COUNTY OR PARISH 13. STATE
Chaves NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3872' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in and rigged up rotary tools. Drilled out plug at 300' and cleaned out hole to bottom of 8-5/8" casing at 1060'. Spudded in at 3:00 AM 12-21-81 with 7-7/8" bit. Washed down.
TD 4160'. Ran 102 joints of 4-1/2" 9.5# casing set at 4160'. 1-Regular pattern guide shoe at 4160'. Float collar set 4119'. Cemented w/600 sacks 50/50 Poz with 2% gel and 2% KCL with .3% Halad-4 and .3% CFR-2. PD 2:45 PM 1-2-82.
Bumped plug to 1000 psi, released pressure and float held okay. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Roger A. Chapman TITLE Engineering Secty DATE 1-4-82

ACCEPTED FOR RECORD (Leave space for Federal or State office use)

ROGER A. CHAPMAN

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 7 1981

U.S. GEOLOGICAL SURVEY
• See Instructions on Reverse Side
ROSWELL, NEW MEXICO