

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>M. C. PETER</u>		Lease <u>HIGHWAY 1475</u>		Well # <u>7</u>	
Location of Well	Unit	Section	Township	Range	County
	<u>10</u>	<u>16</u>	<u>10</u>	<u>3</u>	<u>Chaparral</u>
Drilling Contractor	Guy SWARTZ		Type of Equipment <u>ROTARY</u>		
APPROVED CASING PROGRAM <u>IN 11-61</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>1 1/4"</u>	<u>12 1/2"</u>			<u>54'</u>	<u>13</u>
<u>9 1/8"</u>	<u>1"</u>	<u>2.3</u>	<u>USED</u>	<u>753'</u>	<u>375 cks.</u>
<u>6 1/4"</u>	<u>From 153' to 453' P.H. - PA. R. 14 Casing - H.A. 553' 6" 1/2'</u>				
Casing Data: <u>No casing was pulled.</u>					
Surface <u> </u> joints of <u> </u> inch <u> </u> # Grade <u> </u>					
(Approved) (Rejected) <u> </u>					
Inspected by <u> </u> date <u> </u>					
Cementing Program					
Size of hole <u> </u> Size of Casing <u> </u> Sacks cement required <u> </u>					
Type of Shoe used <u> </u> Float collar used <u> </u> Btm 3 jts welded <u> </u>					
TD of hole <u>52'</u> Set <u> </u> Feet of <u> </u> Inch <u> </u> # Grade <u> </u>					
New-used csg. @ <u> </u> with <u> </u> sacks neat cement around shoe					
+ <u> </u> sax <u> </u> additives <u> </u>					
Plug down @ <u> </u> (AM) (PM) Date <u> </u>					
Cement circulated <u> </u> No. of Sacks <u> </u>					
Cemented by <u> </u> Witnessed by <u> </u>					
Temp. Survey ran @ <u> </u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u>plugging</u> Witnessed by <u>LOBLEY</u>					
Remarks: <u>WELL TO BE PLUGGED WITH MOD. BENTONITE PLUG</u>					
<u>Hole was loaded with bentonite between plugs - 12-4-62. H.K.</u>					
<u>10 1/4" 14 1/2" 16 1/2" 18 1/2" 20 1/2" 22 1/2" 24 1/2" 26 1/2" 28 1/2" 30 1/2" 32 1/2" 34 1/2" 36 1/2" 38 1/2" 40 1/2" 42 1/2" 44 1/2" 46 1/2" 48 1/2" 50 1/2" 52 1/2" 54 1/2" 56 1/2" 58 1/2" 60 1/2" 62 1/2" 64 1/2" 66 1/2" 68 1/2" 70 1/2" 72 1/2" 74 1/2" 76 1/2" 78 1/2" 80 1/2" 82 1/2" 84 1/2" 86 1/2" 88 1/2" 90 1/2" 92 1/2" 94 1/2" 96 1/2" 98 1/2" 100 1/2"</u>					

was plugged as follows

- 25 sbs TD. 12-4-62 H.L.
- 5 sbs at surface OK. 12-4-62

Marker is in and location cleaned.