



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED

WELL RECORD

AUG 4 1961

O. O. O.

ARTESIA, OFFICE

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

J. (Operator/Admistrator)

Mary Ann Canaan (Lease)

Well No. 2, in 1/4 of 27, of Sec. 108, T. 23E, R. 23E, NMPM.

South Bitter Lake, San Andres

Well is 661 feet from line and 1980 feet from line

of Section 27. If State Land the Oil and Gas Lease No. is

Drilling Commenced July 7, 1960 Drilling was Completed July 22, 1960

Name of Drilling Contractor Steinberger Drilling Company

Address Roswell, New Mexico

Elevation above sea level at Top of Tubing Head 3475.1 The information given is to be kept confidential until

OIL SANDS OR ZONES

No. 1, from 926 to 930 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 80 to feet

No. 2, from to feet

No. 3, from to feet

No. 4, from to feet

Casing Record

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SEGE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7	24	Used	900	Larkin			
4 1/2	11.0	Used	960	HISCO		916-913	

Drilling and Cementing Record

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
9 5/8	7	576	220	B & J		
4 1/2	6 1/2	960	92	HISCO		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Broke formation with 500 gallons acid, followed with 10000 gallons of lease crude and 10000 lbs. of fracture sand. After full recovery of treating fluid this well pumped and flowed 36 barrels of oil and 7 barrels of water in 24 hrs.

Result of Production Stimulation

Depth Cleaned Out

RD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 - 960 feet to feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 3, 19 60

OIL WELL: The production during the first 24 hours was 43 barrels of liquid of which 97 % was
was oil; % was emulsion; 3 % water; and % was sediment. A.P.I.
Gravity. 21

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian.	T. Ojo Alamo.
T. Salt.	T. Silurian.	T. Kirtland-Fruitland.
B. Salt.	T. Montoya.	T. Farmington.
T. Yates.	T. Simpson.	T. Pictured Cliffs.
T. 7 Rivers.	T. McKee.	T. Menefee.
T. Queen.	T. Ellenburger.	T. Point Lookout.
T. Grayburg.	T. Gr. Wash.	T. Mancos.
T. San Andres. 516	T. Granite.	T. Dakota.
T. Glorieta.	T.	T. Morrison.
T. Drinkard.	T.	T. Penn.
T. Tubbs.	T.	T.
T. Abo.	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	85	85	Gypsum				
85	390	305	Red Beds				
390	515	125	Brown Lime and Anhy				
515	943	428	San Andres Lime and Anhy.				
943	960	17	Hard gray lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

August 2, 1961

(Date)

Company or Operator J. F. McAdams - ETAL

Address P. O. Box 1716 Hobbs, New Mexico

Name J. F. McAdams

Position or Title Operator