

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRORATION OFFICE	
OPERATOR	

Copy () 1/100 1-100

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

RECEIVED									
JAN 18 1961									
D.C.C. OFFICE									
ARTESIA									

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE If State Land submit 6 Copie.

J. F. McAdams

(Company or Operator)

Mary Ann Gannon

(Lease)

Well No. 3, in NW 1/4 of SW 1/4, of Sec. 27, T. 10S, R. 25E, NMPM.

South Bitter Lake

SA

Pool,

Chaves

County.

Well is 1980 feet from South line and 660 feet from West line

of Section 27. If State Land the Oil and Gas Lease No. is

Drilling Commenced 11-28-60, 19. Drilling was Completed 12-1-60, 19.

Name of Drilling Contractor Charlie Green Drilling Company

Address P. O. Box 635, Jacksboro, Texas

Elevation above sea level at Top of Tubing Head 3473.1 The information given is to be kept confidential until

, 19.

OIL SANDS OR ZONES

No. 1, from 836 feet to 850 feet No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
7"	20#	Used	823'	Halliburton		None	Surface Pipe
4 1/2"	11.6#	New	836'	"			Oil String
2 3/8"	4.7#	Used	850'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
9 5/8"	7"	823'	350	Halliburton Pump	160	110000 (Cement Circulated)

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Sand-Free 165 barrels oil, 10,000 lbs. sand, 550 gal. propane

Interval treated - 836 to 850

Result of Production Stimulation 25 barrel - swab test - 24 hr.

Depth Cleaned Out T.D.

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from Surface feet to 867 feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Company or Operator..... **J. F. Meidams** Address..... **P. O. Box 1716, Hobbs, New Mexico**
Name..... **A. B. Wells** Position or Title..... **Superintendent of Production**
Date..... **January 12, 1966**