NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for sperts on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL	REPORT ON PULLING OR OTHERWISE	:
TREATMENT OF WELL REPORT ON RESULT OF TEST OF CASING	ALTERING CASING REPORT ON DEEPENING WELL	
SHUT-OFF REPORT ON RESULT OF PLUGGING OF WELL	REFORT ON DESTENDING WELL	
X	1	
OIL CONSERVATION COMMISSION Santa Fe, New Mexico. Gentlemen:	Plate Date	1940
Following is a report on the work done and the results	obtained under the heading noted above at	the
Meither et al	Smith RA-1737 Well No. A-1	in the
Company or Operator C. SN NE SE of Sect30	Lease	
Wild Cat Field, Chaves		
The dates of this work were as follows:		
Notice of intention to do the work was (was not) submi		
and approvalof the proposed plan was (was not) obtain	,	
Ripped 5" 0. D. pipe at 800° and 7" at 60 and obtained mud returns from 800° to sur 630° on top of 5" pipe and pumped 20 sack	face. Set drill pipe at	ipe
Ripped 5" 0. D. pipe at 800° and 7" at 60° and obtained mud returns from 800° to sur 630° on top of 5" pipe and pumped 20 sack to 800°. Pulled drill pipe to 600° and pat that depth. Ran 10 sacks coment at su 20 tons of mud in the operation.	Ot. Pumped mud through drill proface. Set drill pipe at a cement under pressure numbed 20 sacks cement in arface. Used approximately	ipe
Ripped 5" 0. D. pipe at 800° and 7" at 60 and obtained mud returns from 800° to sur 630° on top of 5" pipe and pumped 20 sack to 800°. Pulled drill pipe to 600° and pat that depth. Ran 10 sacks cement at su	Ot. Pumped mud through drill proface. Set drill pipe at a cement under pressure numbed 20 sacks cement in arface. Used approximately	ipe Title
Ripped 5" 0. D. pipe at 800° and 7" at 60° and obtained mud returns from 800° to sur 630° on top of 5" pipe and pumped 20 sack to 800°. Pulled drill pipe to 600° and rat that depth. Ran 10 sacks cement at su 20 tons of mud in the operation. Witnessed by Name Subscribed and sworn to before me this 18 day of September , 1910 Maxwa Ball Notary Public	Company I hereby swear or affirm that the inabove is true and correct Name Position Representing MEITHER, ET AL Company	Title formation given
Ripped 5" 0. D. pipe at 800° and 7" at 60° and obtained mud returns from 800° to sur 630° on top of 5" pipe and pumped 20 sack to 800°. Pulled drill pipe to 600° and rat that depth. Ran 10 sacks cement at su 20 tons of mud in the operation. Witnessed by	Company I hereby swear or affirm that the in above is true and correct. Name Position Owner Representing MailThur, ET AL	Title formation given

en kantalan di Ka

and the state of t

A PARTIE DE LA PROPERTIE DE LA