

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR ~~CEMENTING~~ ^{PLUGGING} OF WELLS

Operator <u>MR. VOLTZ</u>		Lease <u>RONALD V. BARBER</u>		Well # <u>I</u>	
Location of Well	Unit <u>NESE</u>	Section <u>9</u>	Township <u>11^S</u>	Range <u>25^E</u>	County <u>Chavez</u>
Drilling Plugging Contractor	<u>STEINBERGER DRG. CO.</u>		Type of Equipment <u>PULLING UNIT</u>		
<u>APPROVED</u> ^{in Hole} CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4"</u>	<u>10 3/4"</u>		<u>-</u>	<u>30'</u>	<u>50 sbs.</u>
<u>8 3/4"</u>	<u>7"</u>			<u>630'</u>	<u>800 circ.</u>
<u>6 1/4"</u>	<u>4 1/2"</u>	<u>9.5 #</u>	<u>New</u>	<u>925'</u>	<u>75 circ.</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____ Size of Casing _____ Sacks cement required _____					
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____					
TD of hole <u>930</u> Set _____ Feet of _____ Inch _____ # Grade _____					
New-used csg. @ _____ with _____ sacks neat cement around shoe					
+ _____ sax _____ additives _____					
Plug down @ _____ (AM) (PM) Date _____					
Cement circulated _____ No. of Sacks _____					
Cemented by _____ Witnessed by _____					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					
<u>Well to be plugged as follows.</u>					

1. 2.5 sbs at T.D. 930' OK. H.L. 3-12-63
2. 2.5 sbs at 650' OK. H.L. 3-12-63
3. 10 sbs at top west marker OK. H.L. 3-12-63

Hole to be loaded with mud between plugs. OK. 3-12-63