

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

| | | | | | |
|---|---|---|--|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | X | REPORT ON RECOMPLETION OPERATION | | REPORT ON (Other) | |

March 11, 1953

Roswell, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Franklin, Aston & Fair

Mabel I. Wilson

(Company or Operator)

(Lease)

1

NE

NW

22

(Contractor)

, Well No. in the 1/4 of Sec.

12 South 25 East

Wildcat

Chaves

T. R. NMPM. Pool, County.

January 6, 1951 and March 10 & 11, 1953

The Dates of this work were as follows:

Notice of intention to do the work (was) (was not) submitted on Form C-102 on, 19, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On completion of drilling and after decision to abandon, a 10 sack plug was placed at the bottom and into the bottom of the 9 5/8" surface string at a depth of 1550 feet. An additional 25 sack plug was placed in and around the casing at 650 feet. Efforts were then made to cut and pull the balance of the casing. This was not successful.

March 9, 1953, a casing pulling crew moved in to salvage as much 9 5/8" as possible. The casing was shot at 400 feet and then shot on up the hole opposite the collars. The pipe finally came free after a shot just below 200'. The hole was filled to surface with gravel and a 25 sack plug was placed at the surface with a 4 foot 4" visual pipe marker.

Witnessed by O. C. Rogers Franklin, Aston & Fair Superintendent
(Name) (Company) (Title)

Approved:

OIL CONSERVATION COMMISSION

B. A. Jameson
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name B. B. Aston

Position Manager

Representing Franklin, Aston & Fair

Address P.O. Box 769 Roswell

(Title)

(Date)