

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

T. S. Stanfield

Monahans, Texas.

Hal Bogle

Company or Operator

Well No.

1

in

NW 1/4 NE 1/4

of Sec.

27

T.

13S.

Lease

R. 25E.

N. M. P. M.

Field,

Cahves

County.

Well is 330 feet south of the North line and 330 feet west of the East line of Sec. 27, Twp. 13S., Rge. 25E.

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Hal Bogle

Address Dexter, New Mexico

If Government land the permittee is

Address

The Lessee is T. S. Stanfield

Address Monahans, Texas.

Drilling commenced Dec. 10 19 39

Drilling was completed

January 13 19 40

Name of drilling contractor T. S. Stanfield

Address Monahans, Texas.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until Sept. 3 19 40

OIL SANDS OR ZONES

No. 1, from 921' to 923'	No. 4, from to
No. 2, from to	No. 5, from to
No. 3, from to	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 720 to 728 feet.	8'
No. 2, from 740 to 750 feet.	10'
No. 3, from 795 to 865 feet.	70'
No. 4, from 1398 to 1400 feet.	2'

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	40#	10	B-Int.	655'	Baker		None		
7"	24#	10	"	1102	"		None		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2"	10	655	20	Rotary pump	12	
8"	7" O.D.	1102	50	Rotary Clay		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

Well was plugged back from 1409' to 880' with mud. Cement plug set at 880'.

Clay used - 5 Tons RECORD OF SHOOTING OR CHEMICAL TREATMENT Cement Used 250 SX

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

John Alexander

Driller

Driller

Alec Flowers

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 4

day of September 19 40

Norma Belle
Notary Public

My Commission expires Nov. 20, 1945

T. S. Stanfield

Date

Name T. S. Stanfield

Position Owner

Representing T. S. Stanfield

Address

Box 1061
Roswell, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	4	4	Soil
4	40	36	Gyp and clay
40	55	15	Rock, hard
55	140	85	Sand, coarse
140	325	185	Gyp & clay
325	625	300	Shale, gumbo & red sand
625	655	30	Rock - set 10" casing
655	720	65	Rock
720	728	8	Rock, water
728	740	12	Rock
740	750	10	Rock, water
750	795	45	Rock
795	865	70	Rock, some water
865	923	58	Lime rock, colored - saturation of oil in rock at 921'
923	1045	122	Lime
1045	1095	50	Lime
1095	1100	5	Water sand
1100	1200	100	Lime
1200	1350	150	Lime
1350	1395	45	Lime
1395	1400	5	Sulphur water sand
1400	1409	9	Lime