

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

NOTES OFFICE 000

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOReswell, New Mexico
(Place)March 28, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Lucas Astor East Reswell State Unit.Franklin, Astor & Fair, Inc.
(Company or Operator)Well No. 1 in K
(Unit)NE $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 35, T. 10 S, R. 26 E, NMPM., Wildest Pool
(40-acre Subdivision)Chaves County.

(Note: Plan approved by Stanley J. Stanley via phone 3/28/55)

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Well was drilled to a total depth of 1655 feet. Flows of fresh water were encountered from 50 to 60 feet and from 90 to 97 feet with total flow of 40 GPM. This is shut off behind the 135 feet of 13 3/8ths inch surface casing. A salt water flow was encountered at 328 to 330 feet with capacity of 30 GPM. A string of 450 feet of 10 3/4 inch casing was run to shut this flow of salt water off. A ten inch hole was drilled from 450 feet on to total depth. Sulphur water at the rate of 150 GPM was encountered at 1620 feet. The hole began to cave and it was obvious that another string of casing would be necessary in order to go deeper. Mr. H.S. Cave, geologist on the well said that the well was running 224 feet low on the San Andres so it was decided to plug and abandon the well. The 450 feet of 10 3/4 inch casing was pulled and the following plugs were set:

- (1) A 25 sack plug at 1600 feet.
- (2) A 25 sack plug at 1000 feet.
- (3) A 25 sack plug at 400 feet.
- (4) A 10 sack plug in the surface casing and cellar. A marker of 7 inch pipe was set in this surface plug.

Approved....., 19.....
Except as follows:Franklin, Astor & Fair, Inc.
(Company or Operator)By R. R. Astor
R.R. Astor
Position General Manager
Send Communications regarding well to:Approved
OIL CONSERVATION COMMISSIONBy S. J. Stanley
Title.....Name R.R. Astor
Address Box 769 Reswell, New Mexico