

# **DUPLICATE** **OIL CONSERVATION COMMISSION** **SANTA FE, NEW MEXICO** **Miscellaneous Reports on Wells**

**RECEIVED**  
**APR 19 1951**  
**OIL CONSERVATION COMMISSION**  
**HOBBS-OFFICE**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

Roswell, N. M. - March 27, 1951

Date

Place

OIL CONSERVATION COMMISSION,  
 SANTA FE, NEW MEXICO.  
 Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Earl G. Levick - Levick/State

Well No. 1 in the

Company or Operator

NAME

of Sec. 26

Lease

T. 9 So.,

R. 26 E.

N. M. P. M.,

Field

Chaves

County.

The dates of this work were as follows:

March 20th and 21st - 1951

Notice of intention to do the work was (was not) submitted on Form C-102 on March 14th 1951.

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## **DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

Hole filled with mud from cement plug on top of the San Andres clay section at 1800' - mudded back to 800' - bridged at that depth and rock and gravel fill up to 510' - 7" pipe cemented in hole and left between 510' up to 585' - rather from 585' up to 510'. Cement plug on top of the 7" pipe at 510'. Plug from 510' up to 495' - mudded and gravel to 325' - cement plug from 325' up to 305' where water had been encountered. Mudded and rock from 305' to 135' - Cement 135' to 115' - mud and plugged to surface with pipe set

Witnessed by Paul Morris Mahres Well Service - Driller

Name

Company

Title

Subscribed and sworn before me this 27th

I hereby swear or affirm that the information given above is true and correct.

day of March, 1951.

Name Earl G. Levick

Position Operator

Representing Earl G. Levick

Company or Operator

Address P. O. Box 1113, Roswell, N.M.

My commission expires March 16, 1952

Remarks:

APPROVED

Date

Roy Garbrough  
 Oil & Gas Inspector

Title

cas line  
7/11/11