

N

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Carl L. Levick, P.O. Box 1113, Roswell, New Mexico

Levick/State Company or Operator 1 Well No. 1 in 1113 of Sec. 36, T. 9 So., R. 26 East Lease Wildcat Field, Chaves County, N. M. P. M.
Well is 660 feet south of the North line and 660 feet west of the East line of Section 36
If State land the oil and gas lease is No. 1-8791 Assignment No. Orig. & 8, 9 & 10
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced August 12th 1950 Drilling was completed March 2 st 1951
Name of drilling contractor Mahres Well Service Address Artesia, N. M.
Elevation above sea level at top of casing 3840 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 130' to 135' feet. 500'
No. 2, from 330' to 335' feet. 800'
No. 3, from 1930' to 1935' feet. 1100'
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
7"	Cemented	510'	to 535'	Left in the hole.					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
2 1/2"		Nitro	15 qts.	3-12-'51	920'	930'
4"		Nitro	50 qts.	3-13-'51	780'	785'

Results of shooting or chemical treatment Nothing showed

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from surface feet to 1940' feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Mahres, Clayton C., Driller Paul Morris, Driller
Drilling Contractor, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13th
day of December 1951.

Notary Public
My Commission expires May 4, 1952

Roswell, N. M., Dec. 13, 1951
Name Carl L. Levick
Position Operator
Representing
Company or Operator
Address P.O. Box 1113, Roswell, N. M.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	60	60	Anhydrite - red sandstone
60	90	30	Red sand
90	110	20	Red shale - red sand
110	140	30	Red sand
140	160	20	Caliche - red shale
160	170	10	Anhydrite - red shale
170	190	20	" " "
190	230	40	Salt - anhydrite
230	310	80	Anhy - red shale - cr. sand
310	340	30	Anhy - cr. sand
340	450	110	Salt - anhy.
450	460	10	Anhy
460	520	60	Salt
520	740	220	Anhy - red shale
740	820	80	Anhy - red shale - red sand
820	840	20	Salt - anhy - red sand
840	850	10	Salt - anhy - red sand
850	860	10	" " "
860	870	10	Red sand
870	940	70	Anhy - red sand
940	970	30	Salt - anhy - red sand
970	1040	70	Anhy - red sand
1040	1070	30	Salt - anhy - red sand
1070	1080	10	Red sand
1080	1270	190	Anhy - red sand
1270	1300	30	Anhy - red shale
1300	1325	25	Salt - anhy (B. A. 1385')
1325	1630	305	Caliche - anhy
1630	1650	20	Del. - anhy - cr. shale
1650	1685	35	Del. - anhy
1685	1715	30	Del. - anhy
1715	1820	105	Del. - anhy.
1820	1850	30	Del.
1850	1895	45	Del. - anhy - red sand of oil.
1895	1940	45	" " " (B. A. 1940. br. cold. water)