

NM OIL COMMISSION
DEPARTMENT OF THE INTERIOR
Artesia, NM 88210
GEOLOGICAL SURVEY

SUBMIT IN TRIF
(Other instruction
verse side)

ATE*
a re

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

No. 18214

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Undesignated

8. FARM OR LEASE NAME

DeKalb Federal

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 21-T8S-R26E

12. COUNTY OR PARISH

CHAVES

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

H.W. Pace

3. ADDRESS OF OPERATOR

P.O. Box 588 Artesia, N.M. 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660" FNL 1980" FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3798 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

8-15-81 Set bridge plug at 6300 Cmt to 6286 perfed Montoya 6253-6261,
6274-6281 with 2 SPF.

8-16-81 Acidized w/ 1500 gal. 15% mud acid 50,000 SCF N₂ @ 3 BPM @
5,000 PSI.

8-17-81 Swabbing wtr/tr oil.

8-19-81 Set retrievable bridge plug @ 6280

8-20-81 Pressured test to 800 PSI perfed Montoya 624-45, 6230-35 w/
2 SPF Acidized w/ 1500 gal. mud acid 40,000 SCF N₂ @ 5,000 PSI.

8-21-81 Swabbing

8-26-81 Ran BHP 985# 16 hours

8-27-81 Swab Dry.

9-2-81 Prep to plug back to Mississippian CIBP Set @ 6200 w/ Cmt
to 6165.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Exploration Manager

DATE Sept. 2, 1981

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side