

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

PLUGGING  
FIELD REPORT FOR ~~CEMENTING~~ OF WELLS

Operator <u>Continental oil co.</u>		Lease <u>STATE KB-22</u>		Well # <u>I</u>	
Location of Well	Unit <u>PSESESE</u>	Section <u>22</u>	Township <u>10<sup>s</sup></u>	Range <u>26<sup>E</sup></u>	County <u>Chaves</u>
<u>PLUGGING</u> <del>Cementing</del> Contractor			Type of Equipment		
<u>in Hole</u> <del>APPROVED</del> CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
	<u>5 1/2</u>	<u>14.0</u>	<u>New</u>	<u>723</u>	<u>50</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole \_\_\_\_\_ Size of Casing \_\_\_\_\_ Sacks cement required \_\_\_\_\_

Type of Shoe used \_\_\_\_\_ Float collar used \_\_\_\_\_ Btm 3 jts welded \_\_\_\_\_

TD of hole 743 Set \_\_\_\_\_ Feet of \_\_\_\_\_ Inch \_\_\_\_\_ # Grade \_\_\_\_\_

New-used csg. @ \_\_\_\_\_ with \_\_\_\_\_ sacks neat cement around shoe  
+ \_\_\_\_\_ sax \_\_\_\_\_ additives \_\_\_\_\_

Plug down @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Cement circulated \_\_\_\_\_ No. of Sacks \_\_\_\_\_

Cemented <sup>plugs</sup> by B.J. Witnessed by LOBLEY

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: well pumped full of cement 5-28-63 H.K.