

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office New MexicoLease No. 02678-A

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	X
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 24, 1958

Ross-Federal
Well No. 14-23 is located 660 ft. from ES line and 1980 ft. from EX line of sec. 23

<u>C SE SW Sec 23</u> (1/4 Sec. and Sec. No.)	<u>T 12 S</u> (Twp.)	<u>R 26 E</u> (Range)	<u>NM PM</u> (Meridian)
<u>Wildcat</u> (Field)	<u>Chaves</u> (County or Subdivision)	<u>New Mexico</u> (State or Territory)	

The elevation of the derrick floor above sea level is 3623 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Filled 7" OD Casing with heavy mud. HOWCO set DB Bridging Basket at 520' (first collar above perforations 560'-65') and dumped 2 sx cement plug 510'-20' on basket. Erected 4" dry hole monument (visibly marked) 4' above ground level with top bull plugged and bottom swaged to 7" OD and screwed same into 7" OD Casing.. Filled cellar and cleaned location of junk.

Permanently plugged and abandoned September 23, 1958.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Intex Oil Company et alAddress 717 Meadows BuildingDallas, TexasBy W. F. Barthelmy
Title Engineer