

DEPARTMENT OF THE INTERIOR

COCICAL SURVEY

B M 10:13

HOBES OFFICE OCC

Regrell, New Mexico

May 4, 1956

Intex Oil Company, et al 717 Headows Building Dallas, Tome

> Re: Lease Las Gruces 064000 Losses Mrs. Pauline V. Trigg

#### Con tlemen:

Receipt is selmouledged of your "Notice of Intention to Drill" dated May 2, 1956, occaring your well No. 1 Trigg-Federal #11-26 on the subject leasehold, 1980 feet from the south line and 1900 feet from the west line of section 26, T. 12 S., R. 26 E., H.M.F.M., Chaves County, New Mexico.

Your proposed work is hereby approved subject to compliance with the provisions of the "Oil and Gas Operating Regulations" revised May 25, 1942, a copy of which will be furnished you upon request and subject to the following conditions:

- 1. Drilling operations so authorized are subject to the attached sheet for general conditions of approval.
- 2. Notify this office in sufficient time to arrange for a representative to witness the commuting operations and the casing and veter simb-off tests.

Very truly yours.

District Engineer

Copy to: NMOCC, Santa Fe/ MCCC, Robbs /



## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL THE

GEOLOGICAL SURVEY

The state of the s responsible for the second

e de la companya de l

్మింగా కో ఇక్షన్స్ కేఫీ కోటోకాక The state of the s Control of the second

TO NAV ARROST CON BOOK ON Control of the second second

10.000 3.00

English and Lindon attach the political support the transfer of the political actions. the second states in the second secon the community of the proof of the second المعالمة المستعدد والمنطوع والأنوال والمستعدد والمستعدد والمتعارض والمتعارض والمستعدد والمستعدد والمتعارض والمت

received the country of the fifth and any property of the country of the second of the second of the second of 

- THE WEST TOOK STORM THE SECOND STORM OF THE SECOND . Come to the Destitution Company and the Landers
- were engagneria out with a mainth than a condition with globable of

The second section is the second 网络山楂的 轉門 医多次激素


> the second state of the contract of the contra en en se la companya de la companya

#### PIEASE READ BEFORE STARTING OF ERATIONS

attention is called to the following general and special requirements for operators on Federal, Indian and acquired land oil and gas leases. Suspension of operations may be required by the District Engineer for failure to comply with the Operating Regulations, the conditions of drilling approval, and these requirements.

#### GENERAL

- l. all drilling and producing wells shall be permanently marked in a constituous place with the name of operator, lease name, serial number of lease, well number, and location. Recessary precautions must be taken to preserve such signs.
- 2. Any change of drilling plan or condition of approval must have approval of the District Engineer BEFORE the change is made.
- 3. Before work is started written approval must be obtained unless other arrangements are made in advance with the District Engineer. After work is completed results must be reported to the U. S. Geological Survey by submitting to the listrict Engineer complete information including the dates the work was done on Form 9-33la (9-331b-Indian), in triplicate, covering:
  - a. Mudding, cementing, and method and results of testing water shut-off. (Show spud date of well on first report submitted),
  - b. Drill-stem tests or perforating.
  - c. Shooting, acid treatment, deepening or plugging back.
  - d. Cusing alterations, packer setting, or relairs of any kind.
  - e. Gas-lift installations.
- 4. Monthly report of operations in duplicate on form 9-329 (9-329a-Indian) must be submitted promptly each month to U. S. Geological Survey, Box 6721, Roswell, New Mexico, beginning with spudding of the first well on a lease and continuing until abandonment of all drilling and producing operations is approved.
- 5. Log, in quadruplicate, on form 9-330, must be submitted to the District Engineer within 15 days of completion, abandonment, or suspension unless operator is otherwise instructed by the District Engineer. The log should include a complete driller's log, descriptions of all cores, results of all drill stem tests, formation tops identified, and all other well information not previously reported. Duplicate copies of all electrical logs, sample logs, drilling time logs, temperature, deviation, and other well surveys also must be filed.
- 6. All wells and lease premises shall be maintained in a workmantike manner with due regard to safety, conservation, and appearance.
- 7. approval of a notice of intention to drill or abandon any well will be rescinded without further notice if drilling or abandonment is not started within 90 days.



#### (SUBMIT IN TRIPLICATE)

# UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office		or gode
Lease No	0640	200
Unit		-6 001 <b>0</b> 1

30-005-00179

NOTICE OF INTENTION TO DRILL		1		<u> </u>	
NOTICE OF INTENTION TO CHAN		SUBSEQU	JENT REPORT OF WATER SHUT-OFF	3	
NOTICE OF INTENTION TO TEST		JOEGLAG	ENT REPORT OF SHOOTING OR AC	IDIZING	
NOTICE OF INTENTION TO RE-DI		SUBSEQU	ENT REPORT OF ALTERING CASING	23	
NOTICE OF INTENTION TO SHOO		-020240	ENT REPORT OF RE-DRILLING OR		
NOTICE OF INTENTION TO PULL			ENT REPORT OF ABANDONMENT	frank ( )	
NOTICE OF INTENTION TO ABANI			ENTARY WELL HISTORY		
				<u> </u>	
(INI	DICATE ABOVE BY CHECK	MARK NATURE OF REP	PORT, NOTICE, OR OTHER DATA)		
		. ***********	Nay 2	, 19 <u> <b>S</b>(</u>	
Trigg-Federal Vell No. 11-26 is lo	cated 1980 ft. f	$rom_{-}$ $S$ line a	and 1980 ft. from W		
HE SW	7 12 8	R 26 E	IN PM		
(½ Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
(Field)	Chave		New More	tien	
(2.1014)	(Cou	inty or Subdivision)	(State or Territory)		
ate names of and expected depth	DET	TAILS OF WO	PRK	ite mudding jobs, cement-	
OO' rotary test. (	DET s to objective sands; showing points, and Objective here;	TAILS OF WO	PRK lengths of proposed casings; indice proposed work)	4-4 3000 t	
nte names of and expected depth  00	DET to objective sands; showing points, and Objective heri I nomes, if we N-60 coming by	rails of wo w sizes, weights, and all other important; zons, Queen rranted, be	PRK lengths of proposed casings; indicaproposed work)  Sand 500'-550'; San  B.S. T. 'd. Approxim	Andres 1300'- ately 150' of	
nte names of and expected depth  OO' retary test.  OO'. All petential  5/8" OD 32.30#    = 15.5# J=55 be	DET to objective sands; showing points, and Objective heri I nones, if we is to coming be the and civent	rails of wo w sizes, weights, and all other important; zons, Queen rranted, be	ORK lengths of proposed casings; indicaproposed work)  Sand 500'-550'; San  D.S.T.'d. Approxim  reulated with camen	Andres 1300'- ately 150' of t and 1500' of	
nte names of and expected depth  00° retary test. (  00°. All petential  5/8° 00 32.30% (  2 15.5% J-55 be (  tential somes (wat-	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	PRK lengths of proposed casings; indice proposed work) Sand 500*-550*; San B.S.T.*d. Approximate replaced with camen fficient cament to	Andres 1300'- ately 150' of t and 1500' of protect all	
nte names of and expected depth  OO' retary test.  OO'. All petential  5/8" OD 32.30#    " 15.5# J-55 be    tential somes (wate ectric log hole at	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	PRK lengths of proposed casings; indicaproposed work)  Sand 500'-550'; San  B.S. T. 'd. Approxim	Andres 1300'- ately 150' of t and 1500' of protect all	
nte names of and expected depth  00° retary test. (  00°. All petential  5/8° 00 32.30% (  2 15.5% J-55 be (  tential somes (wat-	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	PRK lengths of proposed casings; indice proposed work) Sand 500*-550*; San B.S.T.*d. Approximate replaced with camen fficient cament to	Andres 1300'- ately 150' of t and 1500' of protect all	
nte names of and expected depth  OO' retary test.  OO'. All petential  5/8" OD 32.30#    " 15.5# J-55 be    tential somes (wate ectric log hole at	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	PRK lengths of proposed casings; indice proposed work) Sand 500*-550*; San B.S.T.*d. Approximate replaced with camen fficient cament to	Andres 1300'- ately 150' of t and 1500' of protect all	
nte names of and expected depth  OO' retary test.  OO'. All petential  5/8" OD 32.30#    " 15.5# J-55 be    tential somes (wate ectric log hole at	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	PRK lengths of proposed casings; indice proposed work) Sand 500*-550*; San B.S.T.*d. Approximate replaced with camen fficient cament to	Andres 1300'- ately 150' of t and 1500' of protest all to total depth ness deemed	
nte names of and expected depth  OO' retary test.  OO'. All petential  5/8" OD 32.30#    " 15.5# J-55 be    tential somes (wate ectric log hole at	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	PRK lengths of proposed easings; indicaproposed work) Sand 500'-550'; San BaS.T.'d. Approxim reulated with cemen fricient cament to wrface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protect all to total depth mes deemed  MAY 4 1056	
nte names of and expected depth 00° retary test. 00°. All petential 5/8° 00 32.30% is 2 15.5% J-55 be is tential somes (water ectric log hole at	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	ork lengths of proposed casings; indicaproposed work)  Sand 500'-550'; San  B.S.T.'d. Approxim reulated with cemen fricient cament to urface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protest all to total depth ness deemed  MAY 4 1956	
nte names of and expected depth  OO' retary test.  OO'. All petential  5/8" OD 32.30#    " 15.5# J-55 be    tential somes (wate ectric log hole at	DET s to objective sands; showing points, and Objective heri l nones, if was limited easing be set and circular 6 oil). Here	rails of wo waizes, weights, and all other important; zons, Queen rranted, be e set and ci ated with su	ork lengths of proposed casings; indicaproposed work)  Sand 500'-550'; San  B.S.T.'d. Approxim reulated with cemen fricient cament to urface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protect all to total depth mes deemed  MAY 4 1050	
of rotary test.  Oo'. All potential  5/8" OD 32.30#    " 15.5# J-55 be itential some (waterie log hole at	DET  to objective sands; showing points, and Objective heri- l nones, if we have the carries in the second circular 6 oil). Here total depth.	rails of Wo waizes, weights, and all other important; zone, Queen rranted, he e set and ci ated with su d up under s To diamond	lengths of proposed easings; indicaproposed work)  Sand 500'-550'; San  BaS.T.'d. Approxim reulated with cemen fricient cament to urface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protect all to total depth nes decmed  MAY 4 1956 G. GEOLOGICAL SURV. SWELL, NEW MEXICO	
of rotary test.  Oo'. All petentia.  5/8" OD 32.30# 1  15.5# J-55 be itential some (waterie log hole at seesary.  understand that this plan of wo	DET  to objective sands; showing points, and Objective heri- l nones, if was  the casing heri- ard circular 6 oil). Huse total depth.	rails of Wo waizes, weights, and all other important; zone, Queen rranted, he e set and ci ated with su d up under s To diamond	ork lengths of proposed casings; indicaproposed work)  Sand 500'-550'; San  B.S.T.'d. Approxim reulated with cemen fricient cament to urface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protect all to total depth nes decmed  MAY 4 1956 G. GEOLOGICAL SURV. SWELL, NEW MEXICO	
of rotary test.  Oo'. All potential  5/8" OD 32.30#    " 15.5# J-55 be itential some (waterie log hole at	DET  to objective sands; showing points, and Objective heri- l nones, if was  the casing heri- ard circular 6 oil). Huse total depth.	rails of Wo waizes, weights, and all other important; zone, Queen rranted, he e set and ci ated with su d up under s To diamond	lengths of proposed easings; indicaproposed work)  Sand 500'-550'; San  BaS.T.'d. Approxim reulated with cemen fricient cament to urface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protect all to total depth nes decmed  MAY 4 1956 G. GEOLOGICAL SURV. SWELL, NEW MEXICO	
of rotary test.  Oo'. All potential  5/8" OD 32.30#    " 15.5# J-55 be itential some (waterie log hole at cessary.  understand that this plan of wo	DET  to objective sands; showing points, and Objective heri- l nones, if was  set and circular 6 oil). Hus  total depth.  ork must receive approval	rails of Wo waizes, weights, and all other important; zone, Queen rranted, he e set and ci ated with su d up under s To diamond	lengths of proposed easings; indicaproposed work)  Sand 500'-550'; San  BaS.T.'d. Approxim reulated with cemen fricient cament to urface and maintain core any some or so	Andres 1300'- ately 150' of t and 1500' of protect all to total depth nes decmed  MAY 4 1956 G. GEOLOGICAL SURV. SWELL, NEW MEXICO	

Title ....

Engineer

INTEX - ABILENE

Bakerslield ------Copy Distribution

5.22.



## John A. Mathis, Jr. SOUTHEAST ENGINEERING CO.

GENERAL SURVEYING

PHOTOSTATS
 OZALID PRINTS

ARTESIA, NEW MEXICO

				h & Wes	t Lines)	
	ed Dist	County	<del>,</del>		NEW MEXI	со
						Ground Elevati
						-3591.31
		0				
						N
						1
						MAY 4 1956
SCALE 4"	= 1 MILE			I		
OF ACTUAL	. SURVEYS M	ADE BY ME (	OR UNDER MY	SUPERVISION	OM FIELD NOTES AND THAT THE GE AND BELIEF.	ROSWELL, NEW MEXIC
			7	_	weken	7

tide of the second

### est, võidist altu ekkir. On okk mateist ola kedor

And the second of the second o

grand and the second

HE KODE ON THE THE SECOND TO THE SECOND TO SEC