

(SUBMIT IN TRIPLICATE)

Lead Office Denver

Lease No. RE-5781 A

Unit _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

ILLEGIBLE

RECEIVED

AUG 29 1960

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 2 is located 660 ft. from S line and 660 ft. from E line of sec. 15
22.5 (Twp.) 21.5 (R.R.) 26.5 (Meridian)
Willard (Field) Sharon (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3800 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

PLANNED PROGRAM

1 1/2" to 2"	10 ft cement
2 1/2" to 3"	Drilling fluid
3 1/2" to 4"	10 ft cement
4 1/2" to 5"	Drilling fluid
5 1/2" to 6"	15 ft cement
6 1/2" to 7"	Drilling fluid
7 1/2" to 8"	15 ft cement
8 1/2" to 9"	Drilling fluid
9 1/2" to 10"	15 ft cement
10 1/2" to 11"	Drilling fluid
11 1/2" to 12"	15 ft cement
12 1/2" to 13"	Drilling fluid
13 1/2" to 14"	15 ft cement
14 1/2" to 15"	Drilling fluid
15 1/2" to 16"	15 ft cement
16 1/2" to 17"	Drilling fluid
17 1/2" to 18"	15 ft cement
18 1/2" to 19"	Drilling fluid
19 1/2" to 20"	15 ft cement
20 1/2" to 21"	Drilling fluid
21 1/2" to 22"	15 ft cement
22 1/2" to 23"	Drilling fluid
23 1/2" to 24"	15 ft cement
24 1/2" to 25"	Drilling fluid
25 1/2" to 26"	15 ft cement
26 1/2" to 27"	Drilling fluid
27 1/2" to 28"	15 ft cement
28 1/2" to 29"	Drilling fluid
29 1/2" to 30"	15 ft cement
30 1/2" to 31"	Drilling fluid
31 1/2" to 32"	15 ft cement
32 1/2" to 33"	Drilling fluid
33 1/2" to 34"	15 ft cement
34 1/2" to 35"	Drilling fluid
35 1/2" to 36"	15 ft cement
36 1/2" to 37"	Drilling fluid
37 1/2" to 38"	15 ft cement
38 1/2" to 39"	Drilling fluid
39 1/2" to 40"	15 ft cement
40 1/2" to 41"	Drilling fluid
41 1/2" to 42"	15 ft cement
42 1/2" to 43"	Drilling fluid
43 1/2" to 44"	15 ft cement
44 1/2" to 45"	Drilling fluid
45 1/2" to 46"	15 ft cement
46 1/2" to 47"	Drilling fluid
47 1/2" to 48"	15 ft cement
48 1/2" to 49"	Drilling fluid
49 1/2" to 50"	15 ft cement
50 1/2" to 51"	Drilling fluid
51 1/2" to 52"	15 ft cement
52 1/2" to 53"	Drilling fluid
53 1/2" to 54"	15 ft cement
54 1/2" to 55"	Drilling fluid
55 1/2" to 56"	15 ft cement
56 1/2" to 57"	Drilling fluid
57 1/2" to 58"	15 ft cement
58 1/2" to 59"	Drilling fluid
59 1/2" to 60"	15 ft cement
60 1/2" to 61"	Drilling fluid
61 1/2" to 62"	15 ft cement
62 1/2" to 63"	Drilling fluid
63 1/2" to 64"	15 ft cement
64 1/2" to 65"	Drilling fluid
65 1/2" to 66"	15 ft cement
66 1/2" to 67"	Drilling fluid
67 1/2" to 68"	15 ft cement
68 1/2" to 69"	Drilling fluid
69 1/2" to 70"	15 ft cement
70 1/2" to 71"	Drilling fluid
71 1/2" to 72"	15 ft cement
72 1/2" to 73"	Drilling fluid
73 1/2" to 74"	15 ft cement
74 1/2" to 75"	Drilling fluid
75 1/2" to 76"	15 ft cement
76 1/2" to 77"	Drilling fluid
77 1/2" to 78"	15 ft cement
78 1/2" to 79"	Drilling fluid
79 1/2" to 80"	15 ft cement
80 1/2" to 81"	Drilling fluid
81 1/2" to 82"	15 ft cement
82 1/2" to 83"	Drilling fluid
83 1/2" to 84"	15 ft cement
84 1/2" to 85"	Drilling fluid
85 1/2" to 86"	15 ft cement
86 1/2" to 87"	Drilling fluid
87 1/2" to 88"	15 ft cement
88 1/2" to 89"	Drilling fluid
89 1/2" to 90"	15 ft cement
90 1/2" to 91"	Drilling fluid
91 1/2" to 92"	15 ft cement
92 1/2" to 93"	Drilling fluid
93 1/2" to 94"	15 ft cement
94 1/2" to 95"	Drilling fluid
95 1/2" to 96"	15 ft cement
96 1/2" to 97"	Drilling fluid
97 1/2" to 98"	15 ft cement
98 1/2" to 99"	Drilling fluid
99 1/2" to 100"	15 ft cement

Buy Hole meter will be erected
location will be cleaned and
pits backfilled.

This plan of work must be approved by the Geological Survey before operations may be commenced.

Company Phillips Petroleum Company

Address Box 766

Artesia, N. M.

By H. M. Lima

Title Well Manager



THE
OFFICE OF THE
ATTORNEY GENERAL
STATE OF NEW YORK
ALBANY

IN SENATE
JANUARY 10, 1906

REPORT
OF THE
COMMISSIONER OF
THE LAND OFFICE
FOR THE YEAR
1905

ALBANY:
J. B. LIPPINCOTT
PRINTERS
1906

RECEIVED JAN 11 1906

1906

1906

1906