



(SUBMIT IN TRIPPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Form No. 50-108.4
Approval expires 12-31-66

Land Ord. 3489211
Lease No. EE 007283
State _____

RECEIVED

DEC 1 1960

SUNDRY NOTICES AND REPORTS ON WELLS

D. C. C.

ARTERIA OFFICE

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHUT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	2
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 12, 1960

Well No. 4 is located 440 ft. from S line and 440 ft. from E line of sec. 15
SESE 11 26

SE SE Sec 15 11 26
(S. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat Shawnee New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3300 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show class, weights, and lengths of proposed casings; indicate reworking jobs, cementing patterns, and all other important proposed work)

Shawnee

0 to 20	10 oz cement
20 to 750	Drilling Mud
750 to 975	15 oz cement
975 to 1100	Drilling Mud
1100 to 1200	15 oz cement
1200 to 1300	Drilling Mud
1300 to 1400	15 oz cement
1400 to 1500	Drilling Mud
1500 to 1600	15 oz cement
1600 to 1700	Drilling Mud
1700 to 1800	15 oz cement
1800 to 1900	Drilling Mud
1900 to 2000	15 oz cement
2000 to 2100	Drilling Mud
2100 to 2200	15 oz cement
2200 to 2300	Drilling Mud
2300 to 2400	15 oz cement
2400 to 2500	Drilling Mud
2500 to 2600	15 oz cement
2600 to 2700	Drilling Mud
2700 to 2800	15 oz cement
2800 to 2900	Drilling Mud
2900 to 3000	15 oz cement
3000 to 3100	Drilling Mud
3100 to 3200	15 oz cement
3200 to 3300	Drilling Mud
3300 to 3400	15 oz cement
3400 to 3500	Drilling Mud
3500 to 3600	15 oz cement
3600 to 3700	Drilling Mud
3700 to 3800	15 oz cement
3800 to 3900	Drilling Mud
3900 to 4000	15 oz cement
4000 to 4100	Drilling Mud
4100 to 4200	15 oz cement
4200 to 4300	Drilling Mud
4300 to 4400	15 oz cement
4400 to 4500	Drilling Mud
4500 to 4600	15 oz cement
4600 to 4700	Drilling Mud
4700 to 4800	15 oz cement
4800 to 4900	Drilling Mud
4900 to 5000	15 oz cement
5000 to 5100	Drilling Mud
5100 to 5200	15 oz cement
5200 to 5300	Drilling Mud
5300 to 5400	15 oz cement
5400 to 5500	Drilling Mud
5500 to 5600	15 oz cement
5600 to 5700	Drilling Mud
5700 to 5800	15 oz cement
5800 to 5900	Drilling Mud
5900 to 6000	15 oz cement
6000 to 6100	Drilling Mud
6100 to 6200	15 oz cement
6200 to 6300	Drilling Mud
6300 to 6400	15 oz cement
6400 to 6500	Drilling Mud
6500 to 6600	15 oz cement
6600 to 6700	Drilling Mud
6700 to 6800	15 oz cement
6800 to 6900	Drilling Mud
6900 to 7000	15 oz cement
7000 to 7100	Drilling Mud
7100 to 7200	15 oz cement
7200 to 7300	Drilling Mud
7300 to 7400	15 oz cement
7400 to 7500	Drilling Mud
7500 to 7600	15 oz cement
7600 to 7700	Drilling Mud
7700 to 7800	15 oz cement
7800 to 7900	Drilling Mud
7900 to 8000	15 oz cement
8000 to 8100	Drilling Mud
8100 to 8200	15 oz cement
8200 to 8300	Drilling Mud
8300 to 8400	15 oz cement
8400 to 8500	Drilling Mud
8500 to 8600	15 oz cement
8600 to 8700	Drilling Mud
8700 to 8800	15 oz cement
8800 to 8900	Drilling Mud
8900 to 9000	15 oz cement
9000 to 9100	Drilling Mud
9100 to 9200	15 oz cement
9200 to 9300	Drilling Mud
9300 to 9400	15 oz cement
9400 to 9500	Drilling Mud
9500 to 9600	15 oz cement
9600 to 9700	Drilling Mud
9700 to 9800	15 oz cement
9800 to 9900	Drilling Mud
9900 to 10000	15 oz cement

Dry Hole Marker erected
Location cleaned and pits backfilled

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Phillips Petroleum Company

Address Box 214

Enterprise, Okla

By H. M. Sims

Title Well Manager

