Form 9-331a
(Feb. 1951)

NOV 3

1959

NERVIEW ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Appi	oval exp	iu No. 42-R3: ires 12-31-60.	58.4.
Land Office	Las	Cruses	
Lease No.	0611	103	
Ponte =			·
LL		' 10	
NO	V 4	1050)

NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE SUBSEQUENT REPORT OF ABANDONMENT. NOTICE OF INTENTION TO ABANDON WELL NOTICE OF INTENTION TO ABANDON WELL	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	
November 2 Federal Chaves	, 19_
ell No. $\frac{1690}{S}$ is located $\frac{1690}{S}$ line and $\frac{1690}{S}$ ft. from $\frac{E}{S}$ line of	sec. 🎎
/45%/4 Sec. 24 138 27% W.M.P.M.	
(14 Sec. No.) (Twp.) (Range) (Meridian)	
(Field) (County or Subdivision) (State or Territory)	
ing points, and all other important proposed work)	n Rivers Liene:
test was drilled to T. D. 1060' ed. Testing in the Queen and Sevention has preven emprefitable, so we desire to plug and abandon as for 1. Enock off and pull all 4 1/2" and 8 3/6" easing possible. 2. Set 5 seek plug 760'-765'. 3. Set 10 seek plug on stub of 4 1/2" 4. Set 15 seek plug in bottom at 8 5/8" pipe 200' - 250' 5. Set top plug 60' - 0' with 40 seeks.	
s test was drilled to T. B. 1068' ed. Testing in the Queen and Severtien has preven unprofitable, so we desire to plug and abandon as for 1. Shock off and pull all 4 1/2" and 8 5/8" casing possible. 2. Set 5 such plug 760'-765'. 3. Set 10 such plug on stub of 4 1/2" 4. Set 15 such plug in bottom at 8 5/8" pipe 200' - 250' 5. Set top plug 60' - 0' with 40 suchs. 6. Erect marker pipe.	
s test was drilled to T. B. 1068' sd. Tusting in the Queen and Severtion has preven suprefitable, so we desire to plug and abandon as for 1. Shock off and pull all 4 1/2" and 8 5/8" ensing possible. 2. Set 3 seek plug 700'-705'. 3. Set 10 seek plug on stub of 4 1/2" 4. Set 15 seek plug on stub of 4 1/2" 5. Set top plug 60' - 0' with 40 seeks. 6. Eyest marker pipe. NOV 3 U. S. GEOLOG ROSWELL, N	E W E - 1959
test was drilled to T. B. 1068' of. Easting in the Queen and Severtion has preven approfitable, so we desire to plug and abandon as for I. Enock off and pull all 4 1/2" and 8 5/8" enoing possible. 2. Set 5 seek plug 760'-765'. 3. Set 10 seek plug on atub of 4 1/2" 4. Set 15 seek plug in bottom at 8 5/8" pipe 260' - 250' D. 5. Set top plug 60' - 0' with 40 seeks. 5. Set top plug 60' - 0' with 40 seeks. 6. Eyest marker pipe. NOV 3 U. S. GEOLOG ROSWELL, N. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be	E W E - 1959
test was drilled to T. B. 1068' of. Easting in the Queen and Severtion has preven approfitable, so we desire to plug and abandon as for I. Enock off and pull all 4 1/2" and 8 5/8" enoing possible. 2. Set 5 seek plug 760'-765'. 3. Set 10 seek plug on atub of 4 1/2" 4. Set 15 seek plug in bottom at 8 5/8" pipe 260' - 250' D. 5. Set top plug 60' - 0' with 40 seeks. 5. Set top plug 60' - 0' with 40 seeks. 6. Eyest marker pipe. NOV 3 U. S. GEOLOG ROSWELL, N. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be	E W E - 1959
test was drilled to T. B. 1068' pd. Topting in the Queen and Sevention has proven unprofitable, so we desire to plug and abandon as for 1. Shock off and pull all 4 1/2" and 8 5/8" easing possible. 2. Set 5 seek plug 760'-765'. 3. Set 10 seek plug on atub of 4 1/2" 4. Set 15 seek plug on atub of 4 1/2" 5. Set top plug 60' - 0' with 40 seeks. 6. Erect marker pipe. NOV 3 U. S. GEOLOG ROSWELL, N	E W E - 1959

 $(\mathbf{r}_{i}, \mathbf{r}_{i}, \mathbf{r$ And Little

. .