

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

Plugging
FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>M.C. PETERS</i>		Lease <i>CALF STATE</i>		Well # <i>I</i>	
Location of Well	Unit <i>SEA 11</i>	Section <i>11</i>	Township <i>10</i>	Range <i>27E</i>	County <i>CHADLER</i>
Drilling Contractor <i>PHUCCING GUY SWARTZ</i>		Type of Equipment <i>ROTARY</i>			
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>6 3/4"</i>	<i>None</i>	<i>-</i>	<i>-</i>	<i>1445</i>	

Casing Data:
Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program
Size of hole _____ Size of Casing _____ Sacks cement required _____
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____
TD of hole *1445* Set _____ Feet of _____ Inch _____ # Grade _____
New-used csg. @ _____ with _____ sacks neat cement around shoe
+ _____ sax _____ additives _____
Plug down @ _____ (AM) (PM) Date _____
Cement circulated _____ No. of Sacks _____
Cemented by _____ Witnessed by _____
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____
Casing test @ _____ (AM) (PM) Date _____
Method Used _____ Witnessed by _____
Checked for shut off @ _____ (AM) (PM) Date _____
Method used _____ Witnessed by _____

Remarks: *well to be plugged as per C-100 approved by*
Mr. L.A. 50, 1961 as follows:

well was plugged as follows.

No. 1 1/2 lbs at TD which is 1445' 1.25 sks T.D. O.K.
then from falling hole with mud 2.5 sks at surface O.K.
before setting log hole in the hole was loaded with mud between plugs.
witnessed by Lolley 12-6-62