

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

JUN 21 1950

RECEIVED
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

June 19, 1950

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

HONOLULU OIL CORPORATION State of New Mexico Well No. 3 in the

Company or Operator NE 1/4 of SE 1/4 of Sec. 13, T. 11-S, R. 27-E, N. M. P. M.,

Chisholm Field Chaves County.

The dates of this work were as follows: June 8, 9, 11, 1950

Notice of intention to do the work was (was not) submitted on Form C-102 on June 5 19 50

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2-3/8" tubing was run to 6554 feet. The well was washed with 500 gallons of mud acid and swabbed to test tank at an average rate of 10 BOPH. The well was then acidized with 2000 gallons of regular acid at 1350 psi. Well flowed at the rate of 40 BOPH after acid. The well was then reacidized with 8000 gallons at 800 psi. Well flowed at rate of 73 BOPH after 8000 gallons acid.

Witnessed by John Gould, Jr. HONOLULU OIL CORPORATION Petroleum Engineer
Name Company Title

Subscribed and sworn before me this 19th

day of June, 19 50

N. F. Simpson N. F. Simpson
Notary Public

My commission expires June 1, 1951

I hereby swear or affirm that the information given above is true and correct.

Name George R. Hay

Position Division Development Geological Engineer

Representing HONOLULU OIL CORPORATION
Company or OperatorAddress P. O. Drawer 1391
Midland, Texas

Remarks:

APPROVED

GAS INSPECTOR

