

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	X
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

March 23, 1950

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

HONOLULU OIL CORPORATION

Well No. 1 in the

Company or Operator

Lease

NW 1/4 of SE 1/4

of Sec. 13T. 11-SR. 27-E

N. M. P. M.,

Wildcat

Field

Chaves County

County.

The dates of this work were as follows: March 15 to March 20, 1950.

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on..... 19.....

and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran Baker bridging plug to 4550'. Perforated 7" casing at 4235' with 4 shots.
Ran Baker retainer to 4197'. Squeezed 400 sax cement behind 7" casing. Found top of cement at 2714' from temperature survey. Drilled out retainer and tested perforations at 1000# for 30 minutes. No pressure drop. Set Baker bridge plug at 2590'. Perforated 7" casing with 4 shots at 2560'. Squeezed 400 sax cement behind 7" casing. Cement circulated to surface.

Witnessed by Bishop Craddock

Name

HONOLULU OIL CORPORATION

Company

Division Superintendent

Title

Subscribed and sworn before me this 23day of March, 1950

N. F. Simpson

N. F. Simpson

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name

George R. HoyPosition Division Development Engineer

Representing

HONOLULU OIL CORPORATION

Company or Operator

P.O. DRAWER 1391

My commission expires June 1, 1950

Address

MIDLAND, TEXAS

Remarks:

Reg. Yuckroff
Name
Title