

			16				

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Steinberger Drilling Company

Hansen State

(Company or Operator) (Lease)

Well No. 1 in SE 16 11 s 27 e
Undesignated Chaves NMPM.
Pool, County.
Well is 2,310 feet from West line and 330 feet from South line
164 E-8754
of Section. If State Land the Oil and Gas Lease No. is
Drilling Commenced Febr. 15 58 Drilling was Completed March 1 58
Name of Drilling Contractor Steinberger Drilling Company
Address Box 1137 Roswell, New Mexico
Elevation above sea level at Top of Tubing Head 3,742 The information given is to be kept confidential until Release, 19

OIL SANDS OR ZONES

No. 1, from 834 to 888 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 112 to 120 feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
5 1/2	15.5	used	930	Float			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
6 3/4	5 1/2	930	100	Pump		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforations: 834-37, 841-44, 857-60 867-70 and 885-88

Fractured with 18,270 gallons of water and 18,270 pounds of 20-40 Sand
Used 52 ball sealers.

Result of Production Stimulation
Depth Cleaned Out

1. JORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 937 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing March 2, 1958
OIL WELL: The production during the first 24 hours was 100 barrels of liquid of which 25% was oil; 37% was emulsion; 75% water; and % was sediment. A.P.I. Gravity 37
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt 112	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers 666	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	410		Red bed and Anhydrite				
410	666		Red bed, Anhydrite and salt				
666	680		Queen Sand, gray				
680	810		Red Sand				
810	910		Penrose Sand gray (Queen)				

OIL CONSERVATION COMMISSION
RESERVOIR DISTRICT OFFICE
New Mexico
Records Section
Operator
Sanitary
Production Office
State Land Office
U.S. Geological Survey
Transportation
F.S.
Rm
1
✓

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

March 13, 1958 (Date)
Company or Operator Steinberger Drilling Co. Address Roswell, New Mexico
Name M. G. Peters Position or Title Co-Owner