



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-E358.4  
Approval expires 12-31-60.

Land Office Santa Fe

Lease No. \_\_\_\_\_

Unit Do Salt Federal "A"

RECEIVED

OCT 25 1962

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

OCTOBER 19, 1962

Well No. 1 is located 200 ft. from N line and 2010 ft. from E line of sec. 10

NE/4 Sec. 10

(1/4 Sec. and Sec. No.)

11-6

(Twp.)

27-E

(Range)

10N

(Meridian)

Capote Queen

(Field)

Chaves

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 2672 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Set 7" water shut off string at 571' and drilled Queen Sand. Obtained salt water in Queen. Drilled to TD 720'. Propose to plug as follows:

1. Pull all recoverable 7" casing.
2. Set 28 sack plug at TD.
3. Build plug at 480' and cap with 10 sz.
4. Mud hole. Build plug at 140' and cap with 8 sz.
5. Place 5 sack plug at surface with marker pipe.
6. Level and clean location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company CHASE PETROLEUM COMPANY

Address 300 GULF BUILDING

MIDLAND, TEXAS

By

Title PRESIDENT