


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office \_\_\_\_\_

Lease No. **NW 01816**

Unit \_\_\_\_\_



SUNDRY NOTICES AND REPORTS ON WELLS

HOBBS OFFICE

|   |   |          |
|---|---|----------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |          |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |          |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF REDRILLING OR REPAIR.....  |          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           | <b>X</b> |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |          |
| NOTICE OF INTENTION TO ABANDON WELL.....            |   |          |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**June 19**, 19**50**

Well No. **1- Federal-Hinkle** is located **660** ft. from **[N]** line and **1980** ft. from **[E]** line of sec. **24**

**NE 1/4 Section 24**

(1/4 Sec. and Sec. No.)

**T-11-S**

(Twp.)

**R-27-E**

(Range)

**NMPN**

(Meridian)

**Wildest**

(Field)

**Chaves**

(County or Subdivision)

**New Mexico**

(State or Territory)

The elevation of the derrick floor above sea level is **3749'** ft. **RDV**

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

No commercial shows of oil or gas were encountered in this well. Well was drilled to total depth of 7315 feet in granite. Well was plugged in following manner: 0-20', 11 sack cement; 20-52' mud; 52-100', 30 sack cement; 100-500', mud; 500-560', 25 sack cement; 560-2005', mud; 2005-2200', 60 sack cement; 2200-6419', mud; 6419-6500', 25 sack cement; 6500-7315' total depth, mud. 8-5/8" casing was cut at 500 feet and pulled. A 4-foot marker was set in the top plug as required by regulation.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **HONOLULU OIL CORPORATION**

Address **P. O. Drawer 1391**

**Midland, Texas**

By **George R. Noy**  
**George R. Noy**

Title **Division Development Engineer**