

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR ^{PLUGGING} ~~CEMENTING~~ OF WELLS

Operator <u>HERSCHEL L. COPELAN, M.D.</u>		Lease <u>PAN-AMERICAN STATE</u>		Well # <u>I</u>	
Location of Well	Unit <u>HEAL C</u>	Section <u>27</u>	Township <u>11 S</u>	Range <u>27 E.</u>	County <u>CHAVEZ</u>
PLUGGING Brilling Contractor	<u>CAP FULTON</u>		Type of Equipment <u>PULLING UNIT</u>		
APPROVED ^{IN HOLE} CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
	<u>4 1/2" *</u>	<u>9.5 #</u>	<u>NEW</u>	<u>1014.5'</u>	<u>CIRCULATED</u>
		<u>*</u>	<u>Perforations</u>	<u>945' to 974'</u>	
Casing Data: <u>T.D. 1015'</u>					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole _____ Size of Casing _____ Sacks cement required _____					
Type of Shoe used _____ Float collar used _____ Btm 3 jts welded _____					
TD of hole _____ Set _____ Feet of _____ Inch _____ # Grade _____					
New-used csg. @ _____ with _____ sacks neat cement around shoe					
+ _____ sax _____ additives _____					
Plug down @ _____ (AM) (PM) Date _____					
Cement circulated _____ No. of Sacks _____					
Cemented by _____ Witnessed by _____					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

No. 1 25 sks at T.D. Witnessed by P4 Nov 1-15-63
 No 2. 20 sks at 300' witnessed by Lobley 1-16-63
 No. 3. 5 sks at surface
 with mud between plugs or else filled with cement
 from T.D. to surface.
 Mud was used between plugs.

CNZ
 sign
 1-103
 2-14-63
 H.H.