



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

JAN 20 1961

WELL RECORD

O. C. C.
ARTESIA, OFFICE

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Wayne J. Spears

Spears-State

(Company or Operator)

(Lease)

Well No. 3, in SW 1/4 of NE 1/4, of Sec. 28, T. 11 South, R. 27 East, NMPM.

Coyote Creek

Underlying

Pool,

Chaves

County.

Well is 1900 feet from North line and 1900 feet from East line

of Section 28. If State Land the Oil and Gas Lease No. is

Drilling Commenced Aug. 16, 1959 Drilling was Completed Sept. 30, 1959

Name of Drilling Contractor Waters Drilling Company

Address Artesia, New Mexico

Elevation above sea level at Top of Tubing Head. The information given is to be kept confidential until Not Confidential, 19.

OIL SANDS OR ZONES

No. 1, from 865 to 900 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
4 1/2"	9.30	New	914'	Halliburton Galvanneal		865-900	Sur & Prod. Strm

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
6 1/2"	4 1/2"	914'	90	circulated to surface		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated with 123,000 lbs. sand and 500 bbls lse. oil

Result of Production Stimulation

914' Depth Cleaned Out

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 214 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing January 20 1961

OIL WELL: The production during the first 24 hours was 9 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 36

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefec
T. Queen 830'	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Cored 830-900 feet being Sandstone, very fine grained, slightly shaly - salt.							

OIL CONSERVATION COMMISSION
ARTESIA DISTRICT OFFICE
No. Copies Received 5
DISTRIBUTION

OPERATOR	NO. FURNISHED
SANTA FE	1
PRORATION OFFICE	1
STATE LAND OFFICE	1
U. S. G. S.	1
TRANSPORTER	1
FILE	1
BUREAU OF MINES	1

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

January 19, 1961

(Date)

Company or Operator Wayne J. Spears

Address 726 Petroleum Bldg., Roswell, NM

Name Betty J. Spina

Position or Title Agent