

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-005-00334

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

VO-4700

7. Lease Name or Unit Agreement Name:

Ambush AWE State

7. Well No.

#1

8. Pool name or Wildcat

Wildcat Ordovician

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-104) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter M : 660 feet from the South line and 660 feet from the West line

Section 12 Township 12S Range 27E NMPM Chaves County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3808' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Re-entry ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

8/10/00 - TD 10'. Moved in and rigged up pulling unit.

8/11/00 - Resumed drilling on surface plug at 1:30 PM.

8/12/00 - TIH with 8-3/4" bit, and clean out to 5-1/2" casing stub at 1617'.

TIH with 4-3/4" bit, tag stub. Start drilling cement, circulating up around surface casing.

8/14/00 - TIH with 7-5/8" slip joint, float collar and 41 joints 7" 23# LTC J55 8rd casing. Slip 5' over stub at 1617'.

Cement with 150 sxs 35/65 + .6% D20 + .5% D44 + 1/4 pps celloflake and 100 sxs C neat. WOC.

8/16/00 - Drilled out cement and float and 11' cement inside 5-1/2" stub. Fell through.

Tagged at 2354'. No cement across San Andres perms 2195-2313'.

8/17-8/20/00 - Drill out cement and clean out hole to TD at 8017'.

Attempt to log. Could not get logging tools past 6295'. Log from 6295' to 2300'.

See Attached

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE January 21, 2002

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY BN TITLE

DATE JAN 30 2002

Conditions of approval, if any:

Yates Petroleum Corporation
Ambush AWE State #1
API 30-005-00334
Section 12 T12S-R27E
Chaves County, NM

Describe proposed or completed operations (continued):

8/21/00 – Run open hole logs 7035-6295' and tie back in with last logs.

8/23/00 – Ran 195 joints 4" 10.46# L-80 casing set at 8003'. Cemented with 1000 sxs PVL with 1 pps D44 + .2% D65 + .3% D167 + .2% D46 + .15% D13. PD at 1:30 PM. WOC.