

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<input checked="" type="checkbox"/>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

July 30, 1953

(Date)

Midland, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Republic Natural Gas Company, et al

(Company or Operator)

J. P. White

(Lease)

Trinity Drilling Company

(Contractor)

Well No. 1 in the SW 1/4 SE 1/4 of Sec. 9

T. 11-S, R. 28-E, NMPM., Wildcat Pool, Graves County.

The Dates of this work were as follows: July 27, 1953

Notice of intention to do the work (was) (was not) submitted on Form C-102 on July 27, 1953, 19.53.

(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The above well was plugged July 27, 1953 with a 65' cement plug from 7050 to 7115' using 20 sax of 15# slurry cement. Total depth of the hole was 7135'. A second 65' cement plug was set from 2289 to 2356' by using 20 sax of 15# slurry cement. A third 65' plug was set from 1566- 1633' with 20 sax of cement. A top plug using 6 sax was set from 13' to 36' (23'). The top of cement is 8" from top of 8 5/8" casing with 4" line pipe plugged and set 3' in the cement with 5' above ground level. Drilling mud, 9.8#, was left between plugs and in bottom 20' of hole.

Casing left in hole:

13 3/8" OD, 48#, H-40, T&C set at 113' and cemented to surface.

8 5/8", OD, 32# & 28#, J-55 & H-40, T&C set at 1596' and cemented to surface.

Witnessed by M. R. Puckett

(Name)

Republic Natural Gas Co.

(Company)

Gauger

(Title)

Approved: OIL CONSERVATION COMMISSION

J. G. Stanley

(Name)

Engineer District 1

(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name W. F. Griffith, W. F. Griffith

Position Petroleum Engineer

Representing Republic Natural Gas Company

Address Box 195, Midland, Texas

SEP 28 1953

JUL 31 1953

(Date)