Land grace who should be be graced by			. Leagth	· ·	Depth set		
cors=-lanced@lanced			_ Sizəlel				
•		<u>ś</u> ri	cotik <mark>e</mark> r	ECCHED.			
20	direct used E	plosive used	Quantity	Date	Depth shot	Depth cleaned out	
			1	-	*	***	
				<u> </u>			
	are of		TOOLS US				
Rotary tools w	ere used from	fee	t to	feet,, a	nd from	feet to feet	
Cuble tools we	re used from _ To	opfee	t to Bottlia	M.L.feet, a	nd from	feet to feet	
turio Parti							
		., 19		Put to pro	ducing	• . UFR2	
The produ	ction for the first	t 24 hours wa	is	parrels of	fluid of which	% was oil; %	
		•	•				
		Gravity, °Bé					
Roals pros	sure, lbs. per sq. i	າ			310 <u>33</u> 2	v. v. 603	
ROCK press	sure, ibs. per sq. i	¥	MPLOYEE	e Signatura	- N. T.		
	<u> </u>	, Driller			die Sisson	Driller	
	54.5	, Driller		•		•	
·			MATION E	ECORD		, Driller	
FROM	TO	TOTAL FE			FORMATIO	N.	
				٠			
A()0 0 14.35 10	71.00 10 71.0 15			d ando: Sandý	red shale		
15	1432 125		- Nou L'Esti	Sand.	SHALE		
125	7/50 13 0		្រី មិនជា	Vol. (
150	1994: 155					.e full W. 145-50	
155	1701.0 285 173.0 330			Sanar	%_GAD	of 20" Csg.	
1	11.17 350		(4-7)	°& Zell	til		
350	21.42 370		0	100			
570	400		G; 2	-8 30 . 1	tio-syons c)⊕, :000 µ , = (3• = = = = = = = = = = = = = = = = = = =	
400	17.00 455 17.11 500			ydrite	and salt	production of the second second	
425 500]			yarıya 'a Jin ya Lim	y diff oo		
515	1200 535			Tari ve.	. T		
535	570		Red	J.L.Le	- Cem. 151	:" Osg C 570° m/50	
			5a3	ks Oem	ent		
570 595	3770 595 3770 600			ğ linə	4 1,1		
300	1100 645		Sal	.			
645	1731 770		L Rea	- Binaile	geromlijano Ç -	-yrae in a a sa	
770	795	i		Agurrae			
795 E00	7010 800 038 8 10		25	e Familia	70• 7 ⁰ -227		
	C 44.7 O ±0			,			
يشافيد بي		EGEVIT REL			26722723	Х 	

(OVER)

C--C7±5

4