

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

J. Don Hudgens, Inc.

State B

Company or Operator

Lease

Well No. 1 in SW/4NW/4 of Sec. 12, T. 13S

R. 28E, N. M. P. M., Wildcat Field, Chaves County.

Well is 1900 feet south of the North line and 660 feet west of the East line of Section 12

If State land the oil and gas lease is No. B-9412 Assignment No. 7 & 8

If patented land the owner is, Address

If Government land the permittee is, Address

The Lessee is J. Don Hudgens, Inc, Address Box 1898, Hobbs, N.Mex.

Drilling commenced Nov. 17 1951 Drilling was completed March 15 1952

Name of drilling contractor Leonard George, Address Hagerman, New Mexico

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 115 to 170 feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13-3/8"	48#		Spang SILS	195' 1"	Baker Texas Pattern			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	13-3/8"	195'		Landed		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet.

Cable tools were used from 0 feet to 195 feet, and from feet to feet.

PRODUCTION

Put to producing 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 9th

day of May, 1952

Notary Public

My Commission expires

Hobbs, New Mexico

May 9, 1952

Place

Date

Name

Position

Vice-President

Representing

J. DON HUDGENS, INC.

Company or Operator.

Address

Box 1898, Hobbs, New Mexico

