NC

SANTA FE, NEW MEXICO

## **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLA	NS NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WEL	L NOTICE OF INTENTION TO PLUG WELL	XX
NOTICE OF INTENTION TO DEEPEN WEI	LL	
	Hobbs, New Muxico February	7, 1952
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico	Place Date	
Gentlemen:		
Following is a notice of intention to do certa:	in work as described below at the DeKalb Agric. Assn.	Inc. and
los Nietos Oil Co. J.	P. Shite Co. Well No. 1-X in	
company or operator	29-E, N. M. P. M., ildcat.	
Chaves		
	ILS OF PROPOSED PLAN OF WORK	
	THE RULES AND REGULATIONS OF THE COMMISSION	
		ate to
e propose to place cement plug (200 sax) with bottom at 8250', place full of heavy mud and will be arough drill pipe.	s with trace of distillate. D.S.T. 9098'-913 wo hours. No other tests indicated oil, gas 30 sax) with bottom at 9000', place a cement ace a cement plug (30 sax) at 2210'. The holleft in that condition. The plugs will be placed alled in the top of the well casing.	or water. plug le is placed
ecovered 6675' sulfur water in the propose to place cement plug (1830 sax) with bottom at 8250', place of heavy mud and will be prough drill pipe.	s with trace of distillate. D.S.T. 9098'-913 we hours. No other tests indicated oil, gas 30 sax) with bottom at 9000', place a cement ace a cement plug (30 sax) at 2210'. The holleft in that condition. The plugs will be placed hecked, a ten sack cement plug will be placed	or water.  plug le is placed  i in the t
ecovered 6675' sulfur water in the propose to place cement plug () 30 sax) with bottom at 8250', place of the propose to place and and will be be proposed and control of heavy mud and will be been plugs have been placed and control of the well and a 4" marker instance.  Approved	s with trace of distillate. D.S.T. 9098'-913 wo hours. No other tests indicated oil, gas 30 sax) with bottom at 9000', place a cement ace a cement plug (30 sax) at 2210'. The hol left in that condition. The plugs will be placed alled in the top of the well casing.  Dekalb agric. Assm. inc.  Company or Operator By  Position Production Supt. Send communications regarding	or water.  plug le is placed  in the t