

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

**MAY 28 1982**

**O. C. D.**  
**ARTESIA, OFFICE**

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator TOM L. INGRAM ✓		8. Farm or Lease Name Moriah
3. Address of Operator P.O. Box 1757, Roswell, NM 88201		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> , <u>1934</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>10-S</u> RANGE <u>29-E</u> NMPM.		10. Field and Pool, or Wildcat <u>Moriah-Atoka Wildcat</u>
15. Elevation (Show whether DF, RT, GR, etc.) 3885 DF		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-8-82:

5 1/2 casing collapsed at 5725. Swaged out casing and cemented with 150 sxs Class "C" w/ 2% CFR-2 & 6# Na Cl per sack. Drilled out cement and tested to 1000 psi for 30 minutes-- held ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Tom Ingram TITLE Operator DATE 5/27/82

APPROVED BY Mike Wilkins TITLE OIL AND GAS INSPECTOR DATE JUN 7 1982

CONDITIONS OF APPROVAL, IF ANY: