

new 114 Comm.

TRIPPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED

APR 29 1953

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, results of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS	<input checked="" type="checkbox"/>	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 28, 1953

(Date)

Midland, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Republic Natural Gas Company, et al

(Company or Operator)

White Ranch

(Lease)

Trinity Drilling Company

(Contractor)

Well No. 2 in the NW 1/4 SW 1/4 of Sec. 34

T. 11S, R. 29E, NMPM, White Ranch Pool, Chaves County.

The Dates of this work were as follows: April 24, 1953

Notice of intention to do the work (was) (was not) submitted on Form C-102 on New Well, 19, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The well was spudded at 3:00 P.M. on 4-23-53 by Trinity Drilling Company and a 17 1/4" hole drilled to 90'. Ran 65.13' of 13 3/8" surface casing and set at 79.43'. Cemented casing with 60 sacks admix (4% gal and 1:1 Perlite), circulated 25 sacks and left 6' cement plug in the bottom of casing. After waiting 24 hours on cement, plug was drilled out and in process of drilling formation, channeling occurred outside casing. On 4-26-53 the surface casing was squeezed with 100 sacks of regular neat cement, circulated 40 sacks and left a 13' cement plug in bottom of casing. After waiting 24 hours on cement, drilled out plug at 9:45 P.M. on 4-27-53, and we are now drilling ahead.

Witnessed by W. F. Griffith Republic Natural Gas Company Petroleum Engineer
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

W. F. Griffith
(Name)
Oil & Gas Inc.
(Title)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: W. F. Griffith
Position: Petroleum Engineer
Representing: Republic Natural Gas Company
Address: Box 195, Midland, Texas

APR 28 1953