ovember 1983)	
omerly 9-331) DEPARIMENT OF THEATHERIUM *ECONOMIC F	Budget Bureau No. 1004-0135 Expires August 31, 1985  5. LEASE DESIGNATION AND SERIAL NO.
BUREAU OF LAND MANAGEMENT	NM 68078
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Use "APPLICATION FOR PERMIT—" for such proposals Carret	7. UNIT AGREEMENT NAME
OIL WELL OTHER MAR 4 1991	S. FARM OR LEASE NAME
NAME OF OPERATOR	Deemar Federal
Stevens Operating Corporation V O. C. D.  ADDRESS OF OPERATOR  ARTESIA, OFFICE	9. WELL NO.
P. O. Box 2408, Roswell, New Mexico 88202	1
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)	10. FIELD AND POOL, OR WILDCAT
At surface	North King Camp Devonian
Surface: 1974 FSL, 1988 FWL Top Prod. Int.: 1947 FSL, 2557 FWL	11. SEC., T., R., M., OR RLK. AND SURVEY OR AREA
Total Depth: 1948 FSL, 2566 FWL	0 T 1/C D 20F
PERMIT NO.   15. ELEVATIONS (Show whether DF, RT, GR, etc.)	Sec. 9, T-14S, R-29E   12. COUNTY OR PARISH   13. STATE
	Orl Day
Check Appropriate Box To Indicate Nature of Notice, Report, or	
NOTICE OF INTENTION TO:	EQUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT MULTIPLE COMPLETE FRACTURE TREATMENT	ALTERING CASING
SHOOT OF ACIDIZE  ABANDON*  SHOOTING OF ACIDIZING  CHANGE PLANS  (Other) Plug back	and redrill X
(Nors: Report resu	ults of multiple completion on Well upletion Report and Log form.)
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent day proposed work. If well is directionally drilled, give subsurface locations and measured and true ver nent to this work.) *	tes, including estimated date of starting any tical depths for all markers and zones perti-
On July 14, 1989 obtained permission from New Mexico Oil Consback from 9899' to 8500', and drill sidetrack hole easterly be proximity, amending NMOCD Order R-8917-A, subject to further	beyond 330' lease line
and hearing process on allowables. Notified BLM representate 9899'-9799', w/35 sxs class "H" Neat, and 8865'-8665', w/70 s 20/40 sd + 3/10 of 1% CFR-3; drilled out, re-cemented 8865'-8 + 5# salt, 20/40 sd + 3/10 of 1% CFR-3. On July 18 drilled onew sidetrack hole.	commission determinations ive. Set cement plugs sxs class "H" + 5# salt, 8610' w/100 sxs class "H"

\*See Instructions on Reverse Side