


DUPLICATE

FORM C-105



NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Grid for well location mapping.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

DeKalb Agricultural Assn., Inc. 306 Lubbock National Bldg. - Lubbock, Texas
Company or Operator Address
Compton-State Well No. 1 in NE/4, NW/4 of Sec. 26 T. 11-S
Lease
R. 27-E, N. M. P. M. Wildcat Field, Chaves County.
Well is 660 feet south of the North line and 3300 feet west of the East line of Section 26
If State land the oil and gas lease is No. B-8443 Assignment No. 2
If patented land the owner is Not Address - - - -
If Government land the permittee is Not Address - - - -
The Lessee is DeKalb Agricultural Assn., Inc. Address Lubbock, Texas
Drilling commenced December 3, 1949 Drilling was completed June 16, 1950
Name of drilling contractor George P. Livermore Inc. Address Lubbock, Texas
Elevation above sea level at top of casing 3,784 feet.
The information given is to be kept confidential until Not 19.

OIL SANDS OR ZONES

No. 1, from No shows to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 225 to 230 feet. Show of brackish water.
No. 2, from 420 to 423 feet. Filled 200' salt water.
No. 3, from 2100 to 2120 feet. 4 bbls/hr. salt water.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13-3/8"	48	8	National	250	Baker	Not	Not	Water shut off.
10-3/4"	32.75	8	National	497	Baker	All Pulled	Not	Water shut off.
8-5/8"	24	8	National	2157	Baker	All Pulled	Not	Water shut off.

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	13-3/8"	250	66	Halliburton	Cement Circulated - No mud.	

PLUGS AND ADAPTERS

Heaving plug—Material Cement Length 20' Depth Set 250
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
	No shooting or treating done.					

Results of shooting or chemical treatment.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from Not feet to feet, and from feet to feet
Cable tools were used from 0 feet to 3350 feet, and from feet to feet

PRODUCTION

Put to producing 19.
The production of the first 24 hours was No production found barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas.
Rock pressure, lbs. per sq. in.

EMPLOYEES

Geo. P. Livermore inc. - cont. Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 16 day of June, 1950.
Notary Public
My Commission expires June 28, 1953.
Name P. J. Miller Date
Position Production Supt.
Representing DeKalb Agric. Assn. Inc. Company or Operator
Address Lubbock, Texas.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	150	150	Sand and shale.
150	500	350	Salt, anhydrite and sand.
500	900	400	Anhydrite & shale.
900	1035	135	Sand & shale
1035	1120	85	Sand (Queen)
1120	1430	310	Sand, shale and anhydrite
1430	2150	730	Anhydrite & Dolomite (San Andres)
2150	2645	495	Lime & Dolomite
2645	2955	310	Sand and Anhydrite (Glorietta)
2955	3200	245	Dolomite and anhydrite
3200	3350	150	Salt, shale, anhydrite and sand.