

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Clarence Angle</u>		Lease <u>Everna Faircloth</u>		Well # <u>I-C</u>	
Location of Well	Unit <u>SSW N</u>	Section <u>32</u>	Township <u>7^S</u>	Range <u>27^E</u>	County <u>Chaves</u>
Drilling Contractor	<u>C.O. Tools</u>		Type of Equipment <u>ROTARY</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11"</u>	<u>8 5/8"</u>	<u>24 #</u>	<u>new</u>	<u>200</u>	<u>80 sbs</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>14 1/2 #</u>	<u>new</u>	<u>2000</u>	<u>50 sbs</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by <u>Not inspected</u> date _____					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required _____					
Type of Shoe used <u>T.P.</u> Float collar used <u>no</u> Btm 3 jts welded _____					
TD of hole <u>167</u> Set <u>167</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade _____					
New used csg. @ <u>167</u> with <u>100</u> sacks neat cement around shoe & casing					
+ _____ sax _____ additives <u>50-50 PZ + 2% GEL</u>					
Plug down @ <u>1:00</u> (PM) (PM) Date <u>11-28-62</u>					
Cement circulated <u>yes</u> No. of Sacks <u>20</u>					
Cemented by <u>HALLIBURTON</u> Witnessed by <u>LOBLEY</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

P.h. # Swift 9-4207