NUMBER OF COPIE	- AECEI			
DIS	TRIBUTIO	N ('		
SANTA FE		1	T	
FILE		1		
U.S.G.S.	7	21	-	
LAND OFFICE			-	
	OIL		1	
TRANSPORTER	GAS	1	1	
PRORATION OFFI	E			
OPERATOR				

Santa Fc, New Mexico

WELL RECORD

 	 	•••	 	
		0		
1				

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE

If State Land submit 6 Copies

feet from feet from If State 2-19 Contput At Top of Tubing 1 to to to to	East Last Last Last Mead 1MPeevation to which to to	28	was Completed The information from SANDS	9-S feet from 2-22 formation given is to RECE FEB tto to	28E NA 28E NA Co North be kept confidential
to	East Land the Oil any Tool Head 3 Head 19 IMPeriod to which to 15	Pool,	was Completed The information from SANDS	feet from 2-22 formation given is to RECE FEB tto tto	be kept confidential
Compater inflow and elections.	E Land the Oil any Tool Head 3 , 19 IMPeriod to whice to	and Gas Lease No. is, 19	was Completed	2-22 formation given is to RECE FEB tto	be kept confidential
Compater inflow and elections.	E Land the Oil any Tool Head 3 , 19 IMPeriod to whice to	and Gas Lease No. is, 19	was Completed	2-22 formation given is to RECE FEB tto	be kept confidential
torto	Head 3 Head 19 IMPerevation to which to to to	854 DIL SANDS OR ZO No. 4, No. 5, No. 6, DRTANT WATER 1 h water rose in hole. 262	The in	formation given is to RECE FEB tto	be kept confidential
torto	Head 3 Head 19 IMPerevation to which to to to	854 DIL SANDS OR ZO No. 4, No. 5, No. 6, DRTANT WATER 1 h water rose in hole. 262	The in	formation given is to RECE FEB tto	be kept confidential
to to to ater inflow and el	Head 3	854 DIL SANDS OR ZO No. 4, No. 5, No. 6, DETANT WATER S h water rose in hole. 262	The instance of the instance o	formation given is to RECE FEB tto ARE to	be kept confidential
toto	IMPeevation to which	854 DIL SANDS OR ZO	fromfrom	FEB tt6	be kept confidential VED 7554
ater inflow and el	IMP(evation to which	No. 4,	fromfrom	FEB 46	1VED
ater inflow and el	tMPe evation to which	DRTANT WATER 1 h water rose in hole. 262	SANDS		
ater inflow and el	tMPe evation to which	DRTANT WATER 1 h water rose in hole. 262	SANDS		
ater inflow and el	tMPe evation to which	DRTANT WATER 1 h water rose in hole. 262	SANDS		
ater inflow and el	tMPe evation to which	DRTANT WATER 1 h water rose in hole. 262	SANDS		
ater inflow and el	tMPe evation to which	DRTANT WATER 1 h water rose in hole. 262	SANDS		
73 70	evation to whic	h water rose in hole.		feet	1
73 70	to	262		feet	
	to	262 23 0		feet	***************************************
	to	230			
	to			feet	······································
		•••••		feet	•
	to	·····		feet	·
			_		:
T NEW OR		KIND OF	CUT AND		1
OT USED	AMOUNT	SHOE	PULLED FROM	PERFORATIONS	PURPOSE
New	41.7	Tex att			surrace
	MIDDE		VC DECOND		14 5
WUFDF			NG RECORD		
SET	OF CEMENT	USED		RAVITY	AMOUNT OF MUD USED
425 1	bu Reg	nalliburto	n \circ .	0	
		vhere no. sacks of cement 25 160 Reg	vere no. sacks method used 25 160 Reg Malliburto	SET OF CEMENT USED G 25 160 Reg Malliburton 8.	VHERE NO. SACKS METHOD MUD SET OF CEMENT USED GRAVITY

AECORD OF DRILL-STEM AND SPECIAL 1. 18

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary to	ools were t	used from	Q	.ieet to	ベーナナー		ind mora		teet to	fcet.
Cable too	ols were us	sed from	·	feet to	•••••	feet, a	nd from		feet to	feet.
					PRODU	CTION	1	k!		
Put to Pi	mducing		***************************************		10					
	•				•					
OIL WE									uid of which	
	was	s oil;	%	was emulsion	n;	•••••	% wate	r; and	% wa	s sediment. A.P.I.
	Gra	avi ty	***************************************	••••					v_{χ}	
GAS WE	TI. Th		during the fort	04 haves			v a b		i de la companya de	
JAS WE							м.С.ў. р	lus		barrels of
	liqu	iid Hydroca	rbon. Shut in Pre	ssurc	lbs.		4		· \	
Length o	of Time Sh	hut in		****			1		हैं। हें हें	-
PLE	ASE IND	DICATE BE	LOW FORMAT	TION TOPS	(IN CON	FORMAN	CE WIT	H GEOGI	RAPHICAL SECTION	V OF STATE).
			Southeastern N				į		Northwestern Ne	
. Anhy	y	29 6	•••••	T. Devoi	nian			Т.	Ojo Alamo	
. Salt.	······	<u> 421</u>	•	T. Siluri	an			Т.	Kirtland-Fruitland	***************************************
. Salt	•••••••••••	56-3		T. Mont	oya		•••••	Т.	Farmington	······
					son				Pictured Cliffs	
			••••••••••		ee				Menefee	
			***************************************		burger				Point Lookout	
-	-				Vash ite				Mancos	
		,							Dakota	
. 01011		· · · · · · · · · · · · · · · · · · ·	***************************************						Penn	1
. Drin	kard			T						
								T.		<u>/</u>
Γ. Tubb	OS			т						······
Γ. Tubl	OS		•••••	T				T.		
Γ. TublΓ. Abo.Γ. Penn	OS			T T				T.		\
Tubb Abo	OS			T T T				T.		\
Tuble. Abo Penn				T T T				T.		
Tubb Abo Penn Miss. From	То	Thickness in Feet	For	TT. TTFOR	RMATIO	N RECO	ORD	T. T. T. T.	Forma	tion
Tubb Abo. Penn Miss. From	То	Thickness in Feet	For Shi & Shi	TT. TTFOR	RMATIO	N RECC	ORD	T. T. T. T.	Forma	
Tubb Abo. Penn Miss. From		Thickness in Feet	For	TT. TTFOR	RMATIO	N RECC	ORD	T. T. T. T.	Shows of o	tion
. Tubb . Abo . Penn . Miss.	То	Thickness in Feet	Shi & shi,	TT. TTFOR	RMATIO	N RECC	DRD To	Thickness in Feet	Shows of o Dolomite, cr stalling	finely
Tubb Abo. Penn Miss. From	То	Thickness in Feet	Shi & shi,	TT. TTFOR	RMATIO	N RECC	DRD To	Thickness in Feet	Shows of o Dolomite, cr stalling anhydrite	finely e, with inclusions
Tubb Abo. Penn Miss. From 0 296	то 296 421	Thickness in Feet 296 125	Sh & sh, Anhy, ch	TT. TT. FOR	eds	N RECC	DRD To	Thickness in Feet	Shows of o Dolomite, cr stalling	finely e, with inclusions
Tubb Abo. Penn Miss. From 0 296	то 296 421	Thickness in Feet	Sh & sh, Anhy, ch hard	T T T. FOR reaction red becar to	eds Mite	From	DRD To	Thickness in Feet	Shows of control Dolomite, cr stalling anhydrite drk grt to Dolomite,	finely e, with inclusions white brn to gry
Tubb Abo. Penn Miss. From 0 296	то 296 421	Thickness in Feet 296 125	Sh & sh, Anhy, cl hard Red fo, s.s., or	T T T. FOR reation red becar to	eds Site	From	DRD To 2270	T. T	Shows of control Dolomite, cr stalling anhydrite drk grt to Dolomite, some suero	finely e, with inclusions white brn to gry eise, brown
Tubb Abo. Penn Miss. From 0 296	то 296 421	Thickness in Feet 296 125	Sh & sh, Anhy, cl hard Red fo, s.s., or polyhali	T T T. FOR read be sear to	eds Lline red	From	DRD To 2270	T. T	Shows of or Dolomite, cr stalling anhydrite drk grt to Dolomite, some suero dolomite u	finely e, with inclusions white brn to gry isc, brown ith little
Tubb. Abo Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red fa, s.s., or polylali to gry s dirty sh	T. T. T. T. FOR mation red becar to tear to te	eds Line o red red	From	DRD To 2270	T. T	Shows of or Dolomite, cr stalling anhydrite drk grt to Dolomite, some suero dolomite up&P good s	finely e, th inclusions white brn to gry isc, brown th little tain in ver
Tubb. Abo Penn. Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb. Abo Penn. Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red fa, s.s., or polylali to gry s dirty sh	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb Abo. Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb Abo. Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb Abo. Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, th inclusions white brn to gry isc, brown th little tain in ver
Tubb Abo. Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb Abo. Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation eds Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb Abo. Penn Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation eds Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little
Tubb T. Abo. T. Penn T. Miss. From 0 296	To 296 421 563 1000	Thickness in Feet 296 125	Red for solvi ali to gry solvi shard	T. T. T. T. FOR mation red becar to describe to describe alterior siles.	eds Mation eds Lline red red ty,	1763	DRD To 2270	T. T	Shows of or stalling anhydrite drk grt to Dolomite, some sucrodolomite with part of the small state smalls.	finely e, with inclusions white brn to gry isc, brown ith little

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED
I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.
(Date)
Company or Operator
Rebey J. Funk Petro. Engr