

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Mr. Sam. G. Dunn</i>		Lease <i>Beagle</i>		Well # <i>3</i>	
Location of Well	Unit <i>9905-331</i>	Section <i>5</i>	Township <i>7</i>	Range <i>26</i>	County <i>Chavez</i>
Drilling Contractor <i>H. E. Gomez</i>	Type of Equipment <i>Rotary</i>				
APPROVED CASING PROGRAM <i>12005A approved 9-17-64</i>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>11</i>	<i>8 3/8</i>	<i>25 #</i>	<i>used</i>	<i>100</i>	<i>will pull</i>
<i>6 3/4</i>	<i>4 1/2</i>	<i>9.5</i>	<i>New 1964</i>	<i>1200</i>	<i>Circulate</i>
Casing Data:					
Surface <i>25</i> joints of <i>1 1/2</i> inch <i>25 #</i> Grade <i>50</i> (Approved) (Rejected)					
Inspected by <i>Robert</i> date <i>9-18-64</i>					
Cementing Program					
Size of hole <i>6 3/4</i> Size of Casing <i>4 1/2</i> Sacks cement required					
Type of Shoe used <i>1 1/2</i> Float collar used <i>1 1/2</i> Btm 3 jts welded					
TD of hole <i>1010</i> Set <i>1 1/2</i> Feet of <i>1 1/2</i> inch <i>25 #</i> Grade <i>Chavez</i>					
New used csg. @ <i>10</i> with <i>300</i> sacks neat cement around shoe					
+ <i>300</i> sax <i>50</i> additives <i>2 1/2</i>					
Plug down @ <i>2:00</i> (AM) (PM) Date <i>9-18-64</i>					
Cement circulated <i>yes</i> No. of Sacks <i>475</i>					
Cemented by <i>Robert</i> Witnessed by <i>Robert</i>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <i>Well is now ready for production</i>					