

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

L. C. 067811A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR H. E. Prince
3. ADDRESS OF OPERATOR 606 N. Atkinson, Roswell, New Mexico
O.C.C. OFFICE

AUG 14 1974

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
2310 feet from the N line and 330 feet from the W. line.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Dale Federal

9. WELL NO.
6

10. FIELD AND POOL, OR WILDCAT

Linda San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

S26-T7S-R26E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH

Chaves

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug and abandon as follows:

T. D. 1543 feet

Run bottom plug with 15 sacks of cement from 1543 feet back to 1422.55 ft.

Cut casing at 706 feet.

Run heavy mud from 1422.55 back to 153 feet.

Run 100 feet plug 50 feet in surface pipe and 50 feet in hole.

17 sacks in surface pipe and 16 sacks in hole.

Run mud from 53 feet back to 10 feet.

Run 10 feet cement plug and set marker.

Clean debris from site.

RECEIVED

JUL 15 1974

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED H. E. Prince

TITLE Owner

DATE 7/12/74

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
AUG 13 1974

R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side