



NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Shell Oil Co.</u>		Lease <u>Cannon</u>		Well # <u>6</u>	
Location of Well	Unit <u>6605+1980w</u>	Section <u>27</u>	Township <u>10</u>	Range <u>25</u>	County <u>Chaves</u>
Drilling Contractor <u>H. J. ...</u>			Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u> <u>10055A</u> <u>2-12-64</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	<u>10 3/4</u>	<u>32.75</u>	<u>new</u>	<u>30</u>	<u>60</u>
<u>9 7/8</u>	<u>7</u>	<u>23</u>	<u>new</u>	<u>710</u>	<u>300</u>
<u>6 1/4</u>	<u>4 1/2</u>	<u>9.5 + 11.6</u>	<u>new</u>	<u>850</u>	<u>100</u>
Casing Data:					
Surface <u> </u> joints of <u>7</u> inch <u>20</u> # Grade <u>3-55 line fitting</u>					
(Approved) (Rejected)					
Inspected by <u> </u> date <u>3.3.64</u>					
Cementing Program					
Size of hole <u> </u> Size of Casing <u> </u> Sacks cement required <u> </u>					
Type of Shoe used <u> </u> Float collar used <u> </u> Btm 3 jts welded <u> </u>					
TD of hole <u>65</u> Set <u>6.5</u> Feet of <u> </u> Inch <u> </u> # Grade <u> </u>					
New-used csg. @ <u>67</u> with <u>50</u> sacks neat cement around shoe					
+ <u>200</u> sax <u>Incor</u> additives <u> </u>					
Plug down @ <u> </u> (AM) (PM) Date <u> </u>					
Cement circulated <u> </u> No. of Sacks <u> </u>					
Cemented by <u> </u> Witnessed by <u> </u>					
Temp. Survey ran @ <u>2:00</u> (AM) (PM) Date <u> </u> top cement @ <u> </u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks <u>4 1/2 inch pipe 100 ft. in diameter on the 1st. some on next joint</u>					
<u>1 1/2 - 2 basket or 4th joint.</u>					