

1. ORDER OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 30 feet to 1038 feet, and from feet to feet.
Cable tools were used from 0 feet to 30 feet, and from feet to feet.

Started injecting

XXXXXXXXXX April 6

PRODUCTION

1964, at 9:14 a.m. (MST).

OIL WELL: The production during the first 24 hours was barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in.

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anhy.
T. Salt.
B. Salt.
T. Yates.
T. 7 Rivers.
T. Queen.
T. Grayburg.
T. San Andres. 652 (+2849)
T. Glorieta.
T. Drinkard.
T. Tubbs.
T. Abo.
T. Penn.
T. Miss.

T. Devonian.
T. Silurian.
T. Montoya.
T. Simpson.
T. McKee.
T. Ellenburger.
T. Gr. Wash.
T. Granite.
T. Slaughter 888 (+2613)
T.
T.
T.
T.

Northwestern New Mexico

T. Ojo Alamo.
T. Kirtland-Fruitland.
T. Farmington.
T. Pictured Cliffs.
T. Menefee.
T. Point Lookout.
T. Mancos.
T. Dakota.
T. Morrison.
T. Penn.
T.
T.
T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	652	652	Sand & Dolo with Gypsum & Anhydrite				
652	888	236	Anhydrite & gypsum with Dolomite				
888	987	99	Dolomite with Anhydrite and Gypsum				
987	1038	51	Limestone with Dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

Company or Operator Shell Oil Company
Name R. A. LOWERY R. A. Lowery
Address P. O. Box 1858, Roswell, New Mexico
Position or Title District Exploitation Engineer
Date April 7, 1964