NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

ł

:

.

.

.

FIELD REPORT FOR CEMENTING OF WELLS

Operator alla.			Lease Cannon				Well #		
Location	Unit Section 5.5+1.32500 27			Townsh		Range	County Chanes		
Drilling Contractor Borness				Type of Equipment Notary					
APPROVED CASING PROGRAM 975 5 H									
Size of Hole Size of Casing		Weight Per Foot		New	v or Used	Depth	Sacks Cement		
121/2	12/12 10 3/4		32.75			new	31	60'	
9 218			23			11	650	300	
6.74	9 218 7		9.5+11.6			10	820	100	
Casing Data:									
Surfacejoints ofinch# Grade									
(Approved) (Rejected)									
Inspected by date									
Cementing Program									
Size of holeSize of CasingSacks coment required									
Type of Shoe used Float collar used Btm 3 jts welded									
TD of hole Set Feet of Inch Grade									
New-used csg. @withsacks neat cement around shoe									
+ 100 sax 14 cor additives 3 1/2 Call 1/2 Charles prese									
Plug down @ $5 + 75^-$ (****) (PM) Date $3 - 25 - 64^-$ Cement circulated N_0 No. of Sacks									
Temp. Survey ran @ ///30(AMB) (PM) Date $3-24 - 4$ top cement @ $302 - 259$ Casing test @(AM) (PM) Date									
Method Used Witnessed by									
Checked for shut off @ (AM) (PM) · Date									
Wethod used Witnessed by									
Remarks: 3/26/64 St 1" + 250 marks 52 3/2 6-6/ 14									
- manufic of gut at and 1125 71									
At sight for a trank for fat be the sur									
and to with 1". FTG 110 FAM your 50 say incor, comment									
stated to greaters. Fina shet does added by a stand,									
this zet i and is lated 19 have and the									
fail of a stall there.									