1	
1	Form 9-331a Budget Burgau No. 42-R358.4. Form Approved.
	(Feb. 1951) (Feb. 1951) (SUBMIT IN TRIPLICATE)
	Loase No. LC 068127
	UNITED STATES
	DEPARTMENT OF THE INTERIOR
	GEOLOGICAL SURVEY
	AP 5!
	SUNDRY NOTICES AND REPORTS ON WELLS
	NOTICE OF INTENTION TO DRILL
	NOTICE OF INTENTION TO TEST WATER SHUT-OFF
	NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
	NOTICE OF INTENTION TO SHOOT OR ACIDIZE
	NOTICE OF INTENTION TO PULL OR ALTER CASING
	NOTICE OF INTENTION TO ABANDON WELL
	(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	May 8, 19 <sup>-64</sup>
	England Federal
	Well No. 2 is located 1980 ft. from $\begin{bmatrix} N \\ Srt \end{bmatrix}$ line and <u>660</u> ft. from $\begin{bmatrix} E \\ M \\ M \end{bmatrix}$ line of sec. <u>30</u>
	SE NE 30 6S 26E NMPM
	(1/2 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
	(1/2 Sec. No.) (Twp.) (Range) (Meridian)
	(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Linda San Andres (Chayes (State or Territory) (Field) (County or Subdivision) (State or Territory)
	(4 Sec. and Sec. No.) Linda San Andres (County or Subdivision) (County or Subdivision) (State or Territory) (State or Territory)
	(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Linda San Andres (Chayes (State or Territory) (Field) (County or Subdivision) (State or Territory)
	(4 Sec. and Sec. No.) Linda San Andres (County or Subdivision) (County or Subdivision) (State or Territory) (State or Territory)
	(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Asec. and Sec. No.) (Twp.) (Range) (Meridian) (County of Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)
	(4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Linda San Andres (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented
	Image Image Image Image   Image Image Image Image Image Image   Image
	Image (Meridian)   Image (Meridian)   Image New Mexico   Image (Meridian)   Image New Mexico   Image (State or Territory)   The elevation of the derrick floor above sea level is ft. DETAILS OF WORK   (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24
	Image (Meridian)   Image (Meridian)   Image New Mexico   Image (Meridian)   Image New Mexico   Image (State or Territory)   The elevation of the derrick floor above sea level is ft. DETAILS OF WORK   (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24
	Image Image Image Image   Image Image Image Image Image Image   Image
	Image Image Image Image   Image Image Image Image Image Image   Image
	(Werditian) (Werditian) (Werditian) (Rew Mexico (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented with 35 sax cement. Cement circulated to surface, cement allowed to set 24 hours before testing 2000# pressure for 30 minutes with no drop.
	(X Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Field) (Field) (Reage) (Meridian) (Field) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented with 35 sax cement. Cement circulated to surface, cement allowed to set 24 hours before testing 2000# pressure for 30 minutes with no drop.
	(K Bec. and Sec. No.) (Twp.) (Range) (Meridian)   Linda San Andres Chaves New Mexico   (Field) (County or Subdivision) (State or Territory)   The elevation of the derrick floor above sea level is ft.   DETAILS OF WORK (State or Territory)   (State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24   hours before testing 2000# pressure for 30 minutes with no drop. Image: Caluer and Content of the content
	(X Sec. and Sec. No.) (Twp.) (Range) (Meridian) (Field) (Field) (Reage) (Meridian) (Field) (State or Territory) The elevation of the derrick floor above sea level is ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment- ing points, and all other important proposed work) Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented with 35 sax cement. Cement circulated to surface, cement allowed to set 24 hours before testing 2000# pressure for 30 minutes with no drop.
	(K Bec. and Sec. No.) (Twp.) (Itango) (Meridian)   Linda San Andres Chaves New Mexico   (Field) (State or Territory)   The elevation of the derrick floor above sea level is ft. DETAILS OF WORK   (State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24   hours before testing 2000# pressure for 30 minutes with no drop. MAN 1 1 1533   U.S. GEOLOGI H. SENTRY U.S. GEOLOGI H. SENTRY   Weiling the intervention of the desting the sentre intervention of the sentre interventintery interventint of the sentre intervention
	(Prop) (Meridian)   (Meridian)   Meridian)   County or Subdivision)   The elevation of the derrick floor above sea level isft.   DETAILS OF WORK   (State names of and expected depths to objective sends; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24   hours before testing 2000# pressure for 30 minutes with no drop.   I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.   Company
	(Wep) (Range) (Meridian) (Twp) (Range) (Meridian) Linda San Andres (County or Subdivision) (State or Territory) The elevation of the derrick floor above sea level is
	(Prop) (Meridian)   (Meridian)   Meridian)   County or Subdivision)   The elevation of the derrick floor above sea level isft.   DETAILS OF WORK   (State names of and expected depths to objective sends; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24   hours before testing 2000# pressure for 30 minutes with no drop.   I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.   Company
	(Prop) (Meridian)   (Meridian)   Meridian)   County or Subdivision)   The elevation of the derrick floor above sea level isft.   DETAILS OF WORK   (State names of and expected depths to objective sends; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)   Well spudded 4/27/64. Set 10 3/4" 40.50 J-55 casing at 183 feet and cemented   with 35 sax cement. Cement circulated to surface, cement allowed to set 24   hours before testing 2000# pressure for 30 minutes with no drop.   I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.   Company